



Livestock Plaza/Sheep Barn

Addendum Issue Date: 8/8/24

Notice:

The following addendum becomes part of the original Plans and Specifications and takes precedence over the items that may conflict. The Bidder shall acknowledge this addendum on the Bid Form. Failure to acknowledge this addendum may cause rejection of the Bid. Refer to the Instructions to Bidders and the Bid Form.

Additional Documents:

Pre-Bid Meeting Minutes
Plan Holders List

Approved Product:

N/A.

General Clarification Items:

1. Bollards are not galvanized.
2. Alternative metal siding can be supplemented if it meets the performance and material requirements specified.
3. South Dakota State Fair is responsible for trimming trees for the relocation of the existing building.
4. The contractor is responsible for coordinating and moving utility lines for the relocation of the existing building.
5. Davis Bacon wages are not required for this project.
6. ARPA Requirements for the project only apply to Alternate #3.
7. Additional insurance is not required for moving the building.
8. The Livestock Shed/Sheep Barn construction site must be secured during events on April 4-6, June 6-8, and July 24-27.
9. The concrete stem wall finish level is specified in the cast in place concrete section of the specifications.
10. Existing Livestock pens are to be removed by the G.C.
11. Existing red building north of the Dex will be removed by The South Dakota State Fair. Along with any trees and exposed concrete.
12. Solid Surface sills will only be applied to W1 window type in the classroom and office.
13. Bids due August 14, 2024 at 2:30 PM CT.

Architectural:

Specifications:

See attached specifications.

Drawings:

The following changes, revisions, or clarifications shall be made to the drawing documents.:

Sheet R-A1.1 Existing Shed Relocation:

General notes are revised.

Sheet T1.3 – Wall and Assembly Types:

Roof Type A revised.

Sheet A3.2 - Enlarged Plans:

Keynote 19 revised.

Sheet A4.1 - Building Elevations:

Material tag for trim have been revised.

Sheet A5.3 - Details:

Details have been revised.

Sheet A6.1 - Interior Elevations:

Material tags for the trim have been revised.

Keynote 19 is revised.

Sheet A7.1 – Schedules & Door Elevations:

LVT-1 flooring revised.

Sheet A7.2 – Door and Window Details:

Door detail revised.

Civil:

Specifications:

N/A.

Drawings:

C3.1 - Quantities & Details

- Updated Quantities Tables

C4.1 - Demolition Plan

- Changed Adjust Existing Rim Elevation note to include (Alternate #3)

C5.1 - Site Grading & Utilities

- Changed 1” Domestic Water Service to 2” Domestic Water Service
- Added Alternate #3 Quantity for 1-1/2” Domestic Water Service to Wash Bay
- Added Landscaping (By Others) to Surfacing Legend

R-C1.1 - Building Relocation Site Plan

- Added Notes & Typical Sections for Building Relocation Sites

Structural:

Specifications:

N/A.

General Clarification Items:

1. The sturdy-wall drill set brackets do not offer any moment (cantilever) capacity and the manufacturer would not approve it for this use. This existing building construction requires moment capacity for its lateral system. The wet set bracket could be epoxied into the concrete pier.
2. The backfill requirements after the below grade portion of the poles are remove loose material and backfill with drainage fill.
3. The height of the stems walls at door openings are down 8” to accommodate slab if alternate 1 is not taken,
4. Columns do not get concrete blockouts if concrete floor alternate is not taken.
5. Structural elevation 100 is civil 1286.00, refer to civil drawings for FFE.

Drawings:

N/A.

Mechanical:

Specifications:

N/A.

Drawings:

Sheet M0.0 – Cover Sheet:

Detail revisions

Sheet M1.1 – Under Floor Wastewater Plan:

Revision to floor drain.

Sheet M1.2 – Water Piping Plan:

Revision to water service line.

Sheet M2.1 – HVAC Plan:

Condensate drain updates.

Electrical:

Specifications:

N/A.

General Clarification Items:

1. The receptacle devices need to be of the water-resistant type. The standard covers are acceptable and do not need to be an in-use type of cover.
2. Conduit and boxes in the barn area can be type PVC, but must be schedule 80 below 8' above finished floor. The EC shall coordinate with the AHJ for what they will accept in the barn area.

Drawings:

N/A.



Pre-Bid Meeting Minutes

Project: Sheep Barn Schematic
Design and Cost Estimate
Proposal

Project No. DA22015

Date: 08/06/2024

of Pages: 3

OSE#: M2319-10X

Sign-In:

Name	Organization	email
Brandon Carda	OSE	Brandon.Carda@state.sd.us
Peggy Besch	SDSF	Peggy.Besch@state.sd.us
Tom Squires	DAG	Thomas@designarcgroup.com
Nick Kummer	DAG	nicholas@designarcgroup.com
Chad Wieseler	Puetz	wieselerc@puetzdesignbuild.com
Aedan Foner	Century	afoner@centurybuildersnd.com
Caleb Malmskog	Century	caleb@centurybuildersnd.com
Brandon Pietz	KyborzCarlson	bpietz@kyborzcarlson.com
Curt Kempt	Curt Heat	curthvac@midconetwork.com
Phil Lee	T.K. Electric	tkelectric@mitchelltelecom.net
Lanny Olson	TLC Olson	lroconstruction@gmail.com
Randy Olson	TLC Olson	
Casey Barngam	Summit Cont.	casey@buildsummit.com
Steven Bultsma	Summit Cont.	
Josh Johnson	Sentry	Joshj@sentryusa.com
Ben Wipf	Wipf Excavating	benwipf@wipfexcavating.com
Michael Jones	Sharpe Enterprises	Mike.jones@sharpe-ent.com
Brian Feistner	Feistner gravel & excavation	bjfeistner@santel.net
Trent Tampani	North Plains Electric	trent@northplainselectric.net
Josh Wendland	Milbank House Movers	joshw@mhmsd.com
Ryan Bena	Lloyd Construction	Ryan.bena@lloydcompanies.com
Tim Davis	Midland	Tdavis.midland@santel.net
Todd Ziebart	Muth	tziebart@muthelectric.com

The following were items reviewed/discussed during this meeting:

Bid Invitation:

- Electronic bids will be accepted by the State Engineer on behalf of the South Dakota Department of Agriculture and Natural Resources at https://www.sd.gov/cs?id=sc_cat_item&sys_id=d543ece647174e9022dc4080236d433a until August 14, 2024 at 2:30 PM CT for the Livestock Plaza/Sheep Barn, South Dakota State Fair, Huron, South Dakota, OSE# M2319--10X.
- Copies of the Plans and Specifications may be obtained by bidders at the office of designArc Group LLC, 2301 W Russell St. Sioux Falls, SD 57104. A/E Contact: Nicholas Kummer, 605-696-7579, nicholas@designarcgroup.com.
- Substantial Completion Date is July 16, 2025. Liquidated Damages are set at \$700 per calendar day.
- Final Completion Date is August 6, 2025. Liquidated Damages are set at \$350 per calendar day.
- Please contact Brandon with the OSE if running into trouble submitting bids.
- Engineers estimate is valued at \$5,800,000 with all alternates accepted.

Project Description:

- The project is located next to the national guard building.
- The existing building will need to be relocated.
- The existing building will be split into two halves.
- One half of the existing building will be to the north and south of the Dex building at the South Dakota State Fair Grounds.
- The existing building columns will be cut, and remaining post and footing will be removed from the site.
- One half of the two building portions will be longer. See Addendum #2 for specific location.
- New siding and end walls will be added to each half. See architectural and structural drawings.
- The New Livestock Plaza/Sheep Barn is an open structure in the penning area.
- This Sheep barn will have a classroom building that includes restrooms, mechanical room, office, classroom, and mezzanine.
- The mezzanine flooring will be changing. Please see addendum #2 for clarification.
- This building is a non-sprinkled open wood truss building.
- Wood truss spacings are set at 4'-0".
- The truss design was split into three pieces. The end two truss have sloped bottom cords.
- We have large fans in the penning area that will pull air towards the peak louvers.
- The peak louvers have fans to help disperse excess heat in the open area.
- The peak also includes a series of alum. windows.
- The interior walls of the penning area are unfinished and non-insulated.

- The interior walls of the penning area will have 4'-0" plywood applied.
- The conditioned classroom will have cooling only and is designed to be weatherized during the winter.
- The interior gyp. In the classroom building will have control joints to prevent cracking.
- The floors will be polished concrete and epoxy inside the classroom building.
- The structure of the penning shed and classroom are designed independently to allow for separate construction schedules for each component.
- The project has three alternates. Please see specifications for the descriptions of these.
- The lighting is split into zones. Please see electrical drawings for clarification.
- The building will have many corde drops for power at the pens.

Site Walkthrough:

- The existing building will only have replacement siding as indicated on the architectural sheet.
- Profile of metal siding doesn't need to match existing siding.
- Existing posts have varying conditions.
- Existing light is to remain. Lighting will need to be removed while moving the building to prevent damage.
- Power lines will need to be lifted during the move. SDSF scope of work.
- Trees will need to be trimmed before the move. SDSF scope of work.
- The existing building to the North of the Dex will be removed by the SDSF along with any trees and exposed site concrete.
- The fence to the east of the Dex building will need to be removed during the move and reinstalled after.
- Please see addendum #2 for location and grading clarifications.

Respectfully Submitted,



Nicholas Kummer; Project Manager/Architectural Associate
designArc Group, LLC

CC:

Attendees listed above

**DOCUMENT 003132
GEOTECHNICAL DATA**

PART 1 - GENERAL

1.1 GEOTECHNICAL DATA

- A. This Document, with its referenced attachments, is part of the Procurement and Contracting Requirements for the Project. They provide Owner's information for Bidders' convenience and are intended to supplement rather than serve in lieu of Bidders' own investigations. They are made available for Bidders' convenience and information. This Document and its attachments are not part of the Contract Documents.
- B. Because subsurface conditions indicated by the soil borings are a sampling in relation to the entire construction area, and for other reasons, Owner, Architect, Architect's consultants, and the firm reporting the subsurface conditions do not warranty the conditions below the depths of the borings or that the strata logged from the borings are necessarily typical of the entire site. Any party using the information described in the soil borings and geotechnical report accepts full responsibility for its use.
- C. Soil-Boring Data for Project, obtained by Geotek Engineering & Testing Services, Inc., dated May 24, 2024, is available for viewing as appended to this section.
- D. A Geotechnical Investigation Report for Project, prepared by Geotek Engineering & Testing Services, Inc., dated June 27, 2024, is available for viewing as appended to this section.
 - 1. The opinions expressed in this report are those of a geotechnical engineer and represent interpretations of subsoil conditions, tests, and results of analyses conducted by a geotechnical engineer. Owner is not responsible for interpretations or conclusions drawn from the data.
 - 2. Any party using information described in the geotechnical report will make additional test borings and conduct other exploratory operations that may be required to determine the character of subsurface materials that may be encountered.

PART 2 - PRODUCTS (Not Used)
PART 3 - EXECUTION (Not Used)

END OF DOCUMENT 003132



**GEOTEK ENGINEERING
& TESTING SERVICES, INC.**

909 East 50th Street North
Sioux Falls, South Dakota 57104
Phone 605-335-5512 Fax 605-335-0773

June 27, 2024

Office of the State Engineer
Joe Foss Building
523 E. Capitol Avenue
Pierre, South Dakota 57501

Attn: Brandon Carda

Subj: Geotechnical Exploration
Proposed Sheep Barn/Shed
South Dakota State Fairgrounds
3rd Street SW
Huron, South Dakota
GeoTek #24-0868

This correspondence presents our written report of the geotechnical exploration program for the referenced project. Our work was performed in accordance with your authorization. We are transmitting an electronic copy of our report for your use.

We thank you for the opportunity of providing our services on this project and look forward to continued participation during the design and construction phases. If you have any questions regarding this report, please contact our office at (605) 335-5512.

Respectfully Submitted,
GeoTek Engineering & Testing Services, Inc.

Jayden Waldner

Jayden Waldner, EIT
Staff Engineer

Daniel R Hanson

Daniel R Hanson, PE
General Manager

TABLE OF CONTENTS

INTRODUCTION..... 4

 PROJECT INFORMATION 4

 SCOPE OF SERVICES 4

SITE & SUBSURFACE CONDITIONS..... 4

 SITE LOCATION & DESCRIPTION 4

 GROUND SURFACE ELEVATIONS & TEST BORING LOCATIONS 5

 SUBSURFACE CONDITIONS 5

 SOIL TYPES 6

 Existing Fill Materials6

 Fine Alluvium Soils.....6

 Mixed Alluvium Soils6

 Coarse Alluvium Soils.....6

 Glacial Till Soils.....7

 WATER LEVELS 7

ENGINEERING REVIEW AND RECOMMENDATIONS 8

 PROJECT DESIGN DATA 8

 BUILDING..... 8

 Discussion8

 Site Preparation - Footings9

 Site Preparation – Floor Slab Areas.....9

 Foundation Loads & Settlement.....10

 Floor Slab & Soil Modulus of Subgrade Reaction10

 Groundwater & Saturated Soils.....10

 Laterally Oversized Footing Excavations.....11

 Excavation – Building11

 Existing Utilities.....11

 Dewatering11

 Coefficient of Friction11

 Retaining Walls12

 Drain Tile Recommendations.....13

 Seismic Site Classification13

 PAVEMENT AREAS 13

 Discussion13

 Initial Subgrade Preparation13

 Pavement Section Thicknesses.....14

 Excavation – Pavement Areas15

 FROST PROTECTION 15

 Footings.....15

 Shallow Footings & Floor Slabs.....15

 Surface Improvements.....16

 MATERIAL TYPES AND COMPACTION LEVELS 16

 DRAINAGE 19

CONSTRUCTION CONSIDERATIONS 19

 GROUNDWATER AND SURFACE WATER 19

 DISTURBANCE OF SOILS 20

COLD WEATHER PRECAUTIONS	20
EXCAVATION SIDESLOPES.....	20
OBSERVATIONS AND TESTING.....	20
EXCAVATION	21
TESTING.....	21
SUBSURFACE EXPLORATION PROCEDURES	22
TEST BORINGS	22
SOIL CLASSIFICATION	22
WATER LEVEL MEASUREMENTS.....	23
LABORATORY TESTS.....	23
LIMITATIONS.....	23
STANDARD OF CARE	24
APPENDIX A	
FIGURE 1 – SITE LOCATION MAP	
FIGURE 2 – TEST BORING LOCATION MAP	
BORING LOGS	
SOILS CLASSIFICATION	
SYMBOLS AND DESCRIPTIVE TERMINOLOGY	

**GEOTECHNICAL EXPLORATION
PROPOSED SHEEP BARN/SHED
SOUTH DAKOTA STATE FAIRGROUNDS
HURON, SOUTH DAKOTA
GEOTEK #24-0868**

INTRODUCTION

Project Information

This report presents the results of the recent geotechnical exploration program for the proposed Sheep Barn/Shed on the South Dakota State Fairgrounds in Huron, South Dakota.

Scope of Services

We performed our work in accordance with our contractual agreement with the Office of State Engineer. The scope of work as presented in this report is limited to the following:

1. To perform eight (8) standard penetration test (SPT) borings to gather data on the subsurface conditions at the project site.
2. To perform laboratory tests that include moisture content, dry density, sieve analysis (#200 sieve wash) and unconfined compressive strength.
3. To prepare an engineering report that includes the results of the field and laboratory tests as well as our earthwork and foundation recommendations for design and construction.

The scope of our work was intended for geotechnical purposes only. This scope of work did not include determining the presence or extent of environmental contamination at the site or to characterize the site relative to wetlands status.

SITE & SUBSURFACE CONDITIONS

Site Location & Description

The site is located at the South Dakota State Fairgrounds (east of the South Dakota Army National Guard Recruiting Building) in Huron, South Dakota. A site location map (Figure 1) is

attached showing the location of the site. The site currently has a building, gravel surfaced areas and asphalt paving areas.

Ground Surface Elevations & Test Boring Locations

The ground surface elevations at the test boring locations were determined by using the finished floor elevation (FFE) of the South Dakota Army National Guard Recruiting Building as a benchmark. An arbitrary elevation of 100.0 feet was used for the benchmark. Based on the benchmark datum, the ground surface elevations at the test boring locations varied from 99.7 feet at test boring 2 to 97.4 feet at test boring 8. A test boring location map (Figure 2) is attached showing the relative location of the test borings as well as the relative location of the benchmark.

Subsurface Conditions

Eight (8) test borings were performed at the project site on June 18, 2024. Of the eight test borings, 6 test borings (test borings 1 through 6) were performed for the building and 2 test borings (test borings 7 and 8) were performed for the pavement areas. The subsurface conditions encountered at the test boring locations are illustrated by means of the boring logs included in Appendix A.

The subsurface profile at the test boring locations consisted of the following soil types: existing fill materials, fine alluvium soils, mixed alluvium soils, coarse alluvium soils and glacial till soils. The existing fill materials were encountered at all of the test borings and extended to depths of 2 feet and 4 ½ feet. The fine alluvium soils were encountered at the test borings 2, 5, 6 and 8 and extended to depths of 4 ½ feet. The mixed alluvium soils were encountered at the test borings 1 and 2 and extended to depths of 7 feet and 9 ½ feet. The coarse alluvium soils were encountered at the test borings 1, 2, 3, 4, 5 and 8 and extended to depths varying from 6 feet to 11 feet. The glacial till soils were encountered at all of the test borings, excluding boring 8, and extended to the termination depth of the borings.

The consistency/relative density of the soils is indicated by the standard penetration resistance (“N”) values as shown on the boring logs. A description of the soil consistency/relative density

based on the “N” values can be found on the attached Soil Boring Symbols and Descriptive Terminology data sheet.

We wish to point out that the subsurface conditions at other times and locations at the site may differ from those found at our test boring locations. If different conditions are encountered during construction, it is important that you contact us so that our recommendations can be reviewed.

Soil Types

Existing Fill Materials

The existing fill materials consisted of lean clay (CL) and lean clay with sand (CL). “N” values within the existing fill materials ranged from 6 to 21. The moisture condition of the existing fill materials was moist.

Fine Alluvium Soils

Fine alluvium soils consist primarily of silt and clay sized particles that have been deposited by moving water. The fine alluvium soils consisted of sandy lean clay (CL). “N” values within the fine alluvium soils were 6 and 8 (consistency of firm). The moisture condition of the fine alluvium soils was moist.

Mixed Alluvium Soils

Mixed alluvium soils consist of a mixture of silt, clay and sand sized particles that have been deposited by moving water. The mixed alluvium soils consisted of silty sand (SM). “N” values within the mixed alluvium soils ranged from 6 to 9 (relative density of loose and medium dense). The moisture condition of the mixed alluvium soils was moist and wet.

Coarse Alluvium Soils

Coarse alluvium soils consist primarily of sand and gravel sized particles that have been deposited by moving water. The coarse alluvium soils consisted of sand (SP) and sand with silt (SP-SM). “N” values within the coarse alluvium soils ranged from 6 to 12 (relative density of

loose and medium dense). The moisture condition of the coarse alluvium soils was moist and waterbearing.

Glacial Till Soils

Glacial till soils consist of silt and clay sized particles with sand and gravel intermixed that have been deposited and consolidated by a glacier. The glacial till soils consisted of lean clay with sand (CL). “N” values within the glacial till soils ranged from 7 to 14 (consistency of firm and stiff). The moisture condition of the glacial till soils was moist and wet.

Water Levels

Measurements to record the groundwater levels were made at the test boring locations. The time and level of the groundwater readings are recorded on the boring logs. Also, a summary of the groundwater levels is shown in Table 1.

Table 1. Groundwater Levels

Test Boring	Ground Surface Elevation, ft	Groundwater Level, ft	Elevation of Groundwater, ft
1	98.2	7.0	91.2
2	97.7	6.0	91.7
3	99.5	9.5	90.0
4	98.3	8.1	90.2
5	99.3	5.5	93.8
6	98.3	7.3	91.0
7	98.8	Dry to the Cave-In Depth	N/A
8	97.4	Dry to the Cave-In Depth	N/A

The water levels may or may not be an accurate indication of the depth or lack of subsurface groundwater. The limited length of observation restricts the accuracy of the measurements. Long term groundwater monitoring was not included in our scope of work.

ENGINEERING REVIEW AND RECOMMENDATIONS

Project Design Data

We understand that the project will consist of constructing the new Sheep Barn/Shed on the South Dakota State Fairgrounds in Huron, South Dakota. The proposed building will be a wood framed slab-on-grade structure. We assume that the finished floor elevation (FFE) of the building will be near 100.0 feet. Based on the assumed FFE, minimal grade changes (1 foot to 2 feet) are expected. We also assume that foundation support for the proposed building will be provided by perimeter footings resting below frost depth and interior footings resting at or slightly below the floor slab. We anticipate light to moderate foundation loads and light floor slab loads for the proposed building. We understand that the building will not be heated.

The project will also consist of constructing new pavement areas. Minimal grade changes are expected in the pavement areas. We expect that the vehicle traffic will consist of automobiles and large trucks.

The information/assumptions detailed in the project design data section are important factors in our review and recommendations. If there are any corrections or additions to the information detailed in this section, it is important that you contact us so that we can review our recommendations with regards to the revised plans.

Building

Discussion

It is our opinion that a spread footing foundation system can be used for support of the proposed building after the recommended site preparation has been performed.

Test borings 1 through 6 were performed for the building. These test borings encountered existing fill materials, fine alluvium soils, mixed alluvium soils, coarse alluvium soils and glacial till soils. It is our opinion that the existing fill materials are not suitable for support of the footings of the proposed building. Also, in our opinion the fine alluvium soils are suitable for

indirect support of the footings while the mixed alluvium soils, coarse alluvium soils and glacial till soils are suitable for direct support of the footings.

Regarding floor slab support, it is our opinion that the majority of the existing fill materials, fine alluvium soils, mixed alluvium soils, coarse alluvium soils and glacial till soils can be used for indirect support of the floor slab.

Additionally, portions of the existing fill materials consisted of clayey soils. The clayey soils are susceptible to frost heave which could cause both cosmetic and structural damage to the building if not heated during the winter months. If portions of the building will not be heated, we recommend that a layer of non-frost susceptible drainage fill be placed beneath the floor slabs. The thickness of the non-frost susceptible drainage fill will be discussed in further detail in the section entitled "*Frost Protection – Floor Slabs*" on page 15 of this report.

Site Preparation - Footings

The site preparation for the footings (interior and exterior) of the proposed building should consist of removing the asphalt pavement, gravel base/surfacing and existing fill materials in order to expose the fine alluvium soils, mixed alluvium soils, coarse alluvium soils and glacial till soil. Additionally, foundation remnants and construction debris associated with the existing/previous structures should be removed. Following the removals, we recommend that an overexcavation be performed to a minimum depth of 12 inches below the bottom-of-footing elevation. The overexcavation can be discontinued if the mixed alluvium soils, coarse alluvium soils and glacial till soils are encountered. Following the removals, we recommend that observations and shallow hand auger borings be performed at the bottom of the excavations. Unstable areas will likely require further excavation. The overexcavated footing areas should be backfilled with granular structural fill or crushed rock up to the bottom-of-footing elevation.

Site Preparation – Floor Slab Areas

The site preparation in the floor slab areas of the building should consist of removing the asphalt pavement, gravel base/surfacing and debris or excavating to a minimum depth of 12 inches below the bottom-of-floor elevation, whichever is greater. Additionally, foundation remnants and

construction debris associated with the existing/previous structures should be removed. The exposed surface should be compacted with a large sheepsfoot roller. We recommend that observations and testing be performed on the materials exposed at the bottom of the excavation. Unstable areas will likely require further excavation. Once the subgrade is approved, a minimum of 12 inches of granular structural fill should be placed and compacted up to the bottom-of-floor elevation. We recommend that the final 6 inches of granular structural fill beneath the floor slab consist of select granular fill.

Again, for unheated portions of the building we recommend that a layer of non-frost susceptible drainage fill be placed beneath the shallow footings and floor slabs. The thickness of the non-frost susceptible drainage fill will be discussed in further detail in the section entitled “*Frost Protection – Floor Slabs*” on page 15 of this report.

Foundation Loads & Settlement

If our recommendations are followed during site preparations, then it is our opinion that the spread footing foundation system can be sized for a net allowable soil bearing pressure of up to 2,000 pounds per square foot (psf). We estimate total settlement of the building to be less than 1 inch and differential settlement to be around ½ inch. Unknown soil conditions at the site that are different from those depicted at the test boring locations could increase the amount of expected settlement. It is our opinion that the recommended bearing pressure should provide a minimum safety factor of 3.0 against shear or base failure.

Floor Slab & Soil Modulus of Subgrade Reaction

If our recommendations are followed during site preparations, then it is our opinion that the floor slab can be designed using a soil modulus of subgrade reaction (k value) of 100 psi/inch.

Groundwater & Saturated Soils

If groundwater or saturated soils are encountered at the bottom of an excavation, then we recommend placing a layer (6 to 12 inches) of drainage rock at the bottom of the excavation prior to the placement of the granular structural fill, select granular fill or footings.

Laterally Oversized Footing Excavations

Where granular structural fill or drainage rock is needed below the footings, the bottom of the excavation should be laterally oversized 1 foot beyond the edges of the footings for each vertical foot of granular structural fill or drainage rock required below the footings (1 horizontal : 1 vertical).

Excavation – Building

All excavations within the footprint of the building should be performed with a track backhoe with a smooth edge bucket. The subgrade within the footprint of the building should not be exposed to heavy construction traffic from rubber tire vehicles. The soils are susceptible to disturbance and can experience strength loss caused by construction traffic and/or additional moisture.

Existing Utilities

Existing utilities within the footprint of the building should be removed and rerouted around the building.

Dewatering

Dewatering may be needed during construction. In areas where clay soils are encountered, it will likely be possible to remove and control water entering the excavations using normal sump pumping techniques. If waterbearing sand soils are encountered, then an extensive dewatering system will likely be needed.

Coefficient of Friction

It is our opinion that a friction factor of 0.45 can be used between the granular structural fill or drainage rock and the bottom of the concrete. The friction values are considered ultimate values. We recommend applying a theoretical safety factor of at least 2.0.

Retaining Walls

We recommend backfilling any retaining walls with free-draining sand. The active lateral earth pressures may be employed only if movement of the walls can be tolerated to reach the active state. A horizontal movement of approximately 1/500 of the height of the wall would be required to develop the active state for granular soils. If the movement on the previous page cannot be tolerated, then we recommend using the at-rest lateral earth pressures to design the walls. The zone of the sand backfill should extend a minimum of 2 feet outside the bottom of the foundation and then extend upward and outward at a slope no steeper than 1:1 (horizontal to vertical). Also, we recommend capping the sand backfill section with 1 foot to 2 feet of clayey soil in areas that will not have asphalt or concrete surfacing to minimize infiltration of surface waters. Table 2 shows the equivalent fluid unit weight values for the various soil types anticipated for this project.

Table 2. Equivalent Fluid Unit Weight Values

Soil Type	At-Rest, pcf		Active, pcf		Passive, pcf	
	Drained	Submerged	Drained	Submerged	Drained	Submerged
Clay	-	-	-	-	220*	115*
Free-Draining Sand (SP)	50	90	35	80	460*	230*

*Value below frost depth – 0 pcf above frost depth.

The passive resistance in front of a retaining wall should not be used in an analysis unless the wall extends well below the depth of frost penetration due to loss of strength upon thawing. In addition, development of passive lateral earth pressure in the soil in front of a wall requires a relatively large rotation or outward displacement of the wall. Therefore, we do not recommend using passive resistance in front of the wall for the analysis.

We recommend that a perimeter backfill drainage system be provided for the retaining walls to collect and remove water and to prevent hydrostatic pressure on the walls. The drainage system should consist of slotted or perforated drainage pipes located at the bottom of the backfill trench. The drainage system should be connected to a suitable means of discharge.

During backfill operations, bracing and/or shoring of the walls may be needed. Only hand-operated compaction equipment should be used directly adjacent to the walls.

Drain Tile Recommendations

Since the building will be slab-on-grade, it is our opinion that drain tile is not needed along the perimeter of the building. However, if portions of the building are below grade, then drain tile should be installed.

Seismic Site Classification

Based on the 2021 International Building Code (IBC), it is our opinion that the site, as a whole, corresponds to a Site Class D (stiff soil – based on the underlying glacial till soils). Also, the ground acceleration values are as follows: $S_s = 0.145$ g, $S_1 = 0.033$ g, $S_{MS} = 0.232$ g, $S_{M1} = 0.079$ g, $S_{DS} = 0.155$ g, $S_{D1} = 0.053$ g. Therefore, the seismic design category is “A”. The ground acceleration values are based on the ASCE 7-16 (referenced standard for 2021 IBC) with Risk Category II/III. If needed, we can provide ground acceleration values for a different design code.

Pavement Areas

Discussion

Test borings 7 and 8 were performed in the pavement areas. In general, fair subgrade conditions were encountered at the test borings. In our opinion, normal subgrade preparation (scarification and recompaction) could be used in the pavement areas, assuming that the site work is performed during drier periods of the year.

Initial Subgrade Preparation

We recommend that the subgrade preparation in the pavement areas consist of removing the existing asphalt pavement, gravel base/surfacing and debris. Following the removals, the subgrade should be prepared by cutting or placing subgrade fill to the design subgrade elevations. Once the design subgrade elevation is achieved, we recommend that the exposed subgrade be scarified and recompacted. The clay subgrade soils should be scarified (with a disc harrow) to a minimum depth of 8 inches and adjusted to a moisture level that is 1 percent to 4

percent below the optimum moisture content as determined by standard Proctor (ASTM:D698). The moisture-conditioned soils should then be compacted.

Prior to the placement of the aggregate base course materials, we recommend that a proof roll be performed on the exposed subgrade with a truck weighing 20 tons to 30 tons. During the proof roll, unstable areas in the subgrade should be delineated from stable areas. An unstable area would be considered a location with at least 1 inch of rutting or deflection. Unstable areas will need additional corrections to provide a uniform and stable subgrade condition. Additional corrections may include the following: moisture conditioning the soils (e.g. drying the soils by scarification), mixing cement with the subgrade soils, an overexcavation to remove and replace the unstable subgrade soils, the placement of a woven geotextile fabric at the subgrade surface, and/or the placement of granular subbase at the subgrade surface. The type of correction performed should be determined after observing the performance of the subgrade during the proof roll test. We expect that stable conditions will be encountered during drier periods of the year, while some unstable conditions could be encountered during wetter periods of the year (late fall and the spring thaw).

Pavement Section Thicknesses

Table 3 shows the recommended pavement section thicknesses based on the subsurface conditions and anticipated traffic loads. We expect that the vehicle traffic will consist of automobiles (car only) and large trucks (heavy duty).

Table 3. Recommended Pavement Section Thicknesses

Pavement Description	Pavement Surfacing, in	Aggregate Base Course, in
Car Only Areas		
Asphalt:	4	8
PC Concrete:	6	6
Heavy Duty Areas		
Asphalt:	5	9
PC Concrete:	8	6

Notes: The pavement sections are based on the assumption that a stable subgrade condition is achieved during construction. A geotextile fabric could be installed beneath the aggregate base course material to extend the life of the pavement.

The asphalt pavement should meet the requirements of sections 320 and 321 for Class G. We recommend the concrete pavement meet the requirements of Section 380 of the SDDOT Standard Specifications. It should be noted that routine maintenance such as crack filling, localized patching, and seal coating should be expected with all pavements in our recommendations. The design sections could be reduced if the owner is willing to assume additional maintenance costs or potentially shorter pavement life.

Excavation – Pavement Areas

If soils with high moisture content levels are encountered, then low-ground pressure construction equipment should be used.

Frost Protection

Footings

We recommend that all footings be placed at a sufficient depth for frost protection. The perimeter footings for heated buildings should be placed such that the bottom of the footing is a minimum of 4 feet below finished exterior grade. Interior footings in heated buildings can be placed beneath the floor slab. Footings for unheated areas and canopies, or footings that are not protected from frost during freezing temperatures, should be placed such that the bottom of the footing is a minimum of 5 feet below finished exterior grade.

Floor Slabs

As previously stated, we understand that the building will be heated during the winter months. It is our opinion that clayey soils have a moderate frost susceptibility. If clay soils are allowed to freeze beneath the buildings (thickened slabs and floor slabs), then the buildings will potentially be subject to both cosmetic and structural damage caused by frost heaving. The thickened slabs and floor slabs should be designed to accommodate the potential frost movements, or non-frost susceptible drainage fill should be placed beneath the thickened slabs and floor slabs.

If movement of the thickened slabs and/or floor slabs cannot be tolerated, then we recommend placing 5 feet of non-frost susceptible drainage fill beneath the thickened slabs/floor slabs. If it is

desired to reduce (but not eliminate) the amount of potential frost heave, the thickness of the non-frost susceptible drainage fill could be reduced. However, we recommend that a minimum thickness of 2 feet of the non-frost susceptible drainage fill be placed beneath the thickened slabs/floor slabs to help minimize frost heave. The thickness could be further reduced; however, this would increase the risk for frost movement.

Surface Improvements

Surface improvements, such as pavements, patios and sidewalks, are potentially subject to both cosmetic and structural damage caused by frost heaving. The surface improvements should be designed to accommodate the potential frost movements, or non-frost susceptible drainage fill should be placed beneath the surface improvements. If movement cannot be tolerated, then we recommend placing non-frost susceptible drainage fill beneath the surface improvements. The non-frost susceptible drainage fill should extend to a depth of 5 feet below the finished exterior grade. If it is desired to reduce (but not eliminate) the amount of potential frost heave, then we recommend consideration be given to placing 2 feet of non-frost susceptible drainage fill beneath the surface improvements.

Material Types and Compaction Levels

Granular Structural Fill – The granular structural fill should consist of a pit-run or processed sand or gravel having a maximum particle size of 3 inches with less than 15 percent by weight passing the #200 sieve. The granular structural fill should be placed in lifts of up to 1 foot in thickness.

Select Granular Fill – The select granular fill should consist of a medium to coarse grained, free-draining sand or rock having a maximum particle size of 1 inch with less than 5 percent by weight passing the #200 sieve. The select granular fill should be placed in lifts of up to 1 foot in thickness.

Drainage Rock – The drainage rock should be crushed, washed and meet the gradation specifications shown in Table 4.

Table 4. Drainage Rock Gradation Specifications

Sieve Size	Percent Passing
1 1/2-inch	100
1-inch	70 – 90
3/4-inch	25 – 50
3/8-inch	0 – 5

Free-Draining Sand – The free-draining sand should have a maximum particle size of 1 inch with less than 5 percent by weight passing the #200 sieve. The free-draining sand should be placed in lifts of up to 1 foot in thickness.

Exterior Foundation Wall Backfill for Slab-on-Grade Structures – We recommend either clay or granular soils be used. Debris, organic material, or over-sized material should not be used as backfill. If granular soils are used in areas that will not have asphalt or concrete surfacing, we recommend capping the granular soils with at least 1 foot to 2 feet of clay soils to minimize infiltration of surface water. The exterior backfill should be placed in lifts of up to 1 foot in thickness.

Interior Foundation Wall Backfill for Slab-on-Grade Structures – We recommend that granular structural fill be used to backfill the interior side of the foundation walls. The interior backfill should be placed in lifts of up to 1 foot in thickness.

Non-Frost Susceptible Drainage Fill – The non-frost susceptible drainage fill should have a maximum particle size of 1 inch, less than 40 percent by weight passing the #40 sieve and less than 5 percent by weight passing the #200 sieve. The non-frost susceptible drainage fill should be placed in lifts of up to 1 foot in thickness.

Subgrade Fill – The subgrade fill should consist of either a granular or clay material. Debris, organic material, or over-sized material should not be used as subgrade fill. If a granular material is used, then it should consist of a pit-run or processed sand or gravel having a maximum particle size of 3 inches. The granular material can be placed in lifts of up to 1 foot in thickness. If a clay material is selected, then it should consist of a non-organic clay. Scrutiny on the clay material's moisture content should be made prior to the acceptance and use. The clay fill should be placed in lifts of up to 6 inches in thickness. The majority of the on-site soils could be used as subgrade

fill. Some drying should be expected with the on-site soils. Organic materials and construction debris should not be used as subgrade fill.

Aggregate Base Course Material – We recommend that the aggregate base course materials meet the requirements of Sections 260 and 882 of the SDDOT Standard Specifications.

Granular Subbase – The granular subbase should consist of crushed quartzite, recycled concrete or a crushed pit-run material meeting the gradation specifications shown in Table 5.

Table 5. Granular Subbase Gradation Specifications

Sieve Size	Percent Passing
4-inch	100
3-inch	70 – 90
2-inch	60 – 80
1-inch	40 – 70
#4	10 – 50
#40	5 – 20
#200	0 – 8

Recommended Compaction Levels – The recommended compaction levels listed in Table 6 are based on a material’s maximum dry density value, as determined by a standard Proctor (ASTM: D698) test.

Table 6. Recommended Compaction Levels

Placement Location	Compaction Specifications
Below Footings	95%
Below Floor Slabs	95%
Exterior Foundation Wall Backfill for Slab-on-Grade Structures	95%
Behind Retaining Walls	95% - 98%
Subgrade Fill in Pavement Areas	95%
Aggregate Base Course in Pavement Areas	97%
Granular Subbase in Pavement Areas	97%
Non-Structural Areas	90%

Notes: Compaction specifications are not applicable with the drainage rock. Compaction testing may not be practical for the granular subbase due to the large aggregate.

Recommended Moisture Levels – The moisture content of the clay backfill materials, when used as backfill around the exterior of a foundation should be maintained within a range of plus or minus 2 percent of the materials' optimum moisture content. When the clay backfill materials are used below a pavement area, or as site grading, the materials' moisture content should be maintained within a range of minus 1 percent to minus 4 percent of the materials' optimum moisture content. The moisture content of the trench backfill soils should be adjusted to a moisture level that is within plus or minus 2 percent of the optimum moisture content. The optimum moisture content should be determined using a standard Proctor (ASTM: D698) test.

The moisture content of the granular backfill materials should be maintained at a level that will be conducive for vibratory compaction.

Drainage

Proper drainage should be maintained during and after construction. The general site grading should direct surface run-off waters away from the excavation. Water which accumulates in the excavation should be removed in a timely manner.

Finished grades around the perimeter of the building should be sloped such that positive drainage away from the building is provided. Also, a system to collect and channel roof run-off waters away from the building is suggested.

CONSTRUCTION CONSIDERATIONS

Groundwater and Surface Water

Water may enter the excavations due to subsurface water, precipitation or surface run off. Any water that accumulates in the bottom of the excavations should be immediately removed and surface drainage away from the excavations should be provided during construction.

Disturbance of Soils

The soils encountered at the test boring locations are susceptible to disturbance and can experience strength loss caused by construction traffic and/or additional moisture. Precautions will be required during earthwork activities in order to reduce the risk of soil disturbance.

Cold Weather Precautions

If site preparation and construction is anticipated during cold weather, then we recommend all foundations, slabs and other improvements that may be affected by frost movements be insulated from frost penetration during freezing temperatures. If filling is performed during freezing temperatures, then all frozen soils, snow and ice should be removed from the areas to be filled prior to placing the new fill. The new fill should not be allowed to freeze during transit, placement and compaction. Concrete should not be placed on frozen subgrades. Frost should not be allowed to penetrate below the footings. If floor slab subgrades freeze, then we recommend the frozen soils be removed and replaced, or completely thawed, prior to placement of the floor slab. The subgrade soils will likely require reworking and recompacting due to the loss of density caused by the freeze/thaw process.

Excavation Sideslopes

The excavations must comply with the requirements of OSHA 29 CFR, Part 1926, Subpart P, "Excavations and Trenches". This document states that the excavation safety is the responsibility of the contractor. Reference to this OSHA requirement should be included in the project specifications.

Observations and Testing

This report was prepared using a limited amount of information for the project and a number of assumptions were necessary to help us develop our conclusions and recommendations. It is recommended that our firm be retained to review the geotechnical aspects of the final design plans and specifications to check that our recommendations have been properly incorporated into the design documents.

The recommendations submitted in this report have been made based on the subsurface conditions encountered at the test boring locations. It is possible that there are subsurface conditions at the site that are different from those represented by the test borings. As a result, on-site observation during construction is considered integral to the successful implementation of the recommendations. We believe that qualified field personnel need to be on-site at the following times to observe the site conditions and effectiveness of the construction.

Excavation

We recommend that a geotechnical engineer or geotechnical engineering technician working under the direct supervision of a geotechnical engineer observe all excavations for foundations, slabs and pavements. These observations are recommended to determine if the exposed soils are similar to those encountered at the test boring locations, if unsuitable soils have been adequately removed and if the exposed soils are suitable for support of the proposed construction. These observations should be performed prior to placement of fill or foundations.

Testing

After the subgrade is observed by a geotechnical engineer/technician and approved, we recommend a representative number of compaction tests be taken during the placement of the structural fill and backfill placed below foundations, slabs and pavements, beside foundation walls and behind retaining walls. The tests should be performed to determine if the required compaction has been achieved. As a general guideline, we recommend at least 1 test be taken for every 2,000 square feet of structural fill placed in building and pavement areas, at least 1 test for every 75 feet to 100 feet in trench fill, and for every 2-foot thickness of fill or backfill placed. The actual number of tests should be left to the discretion of the geotechnical engineer. Samples of proposed fill and backfill materials should be submitted to our laboratory for testing to determine their compliance with our recommendations and project specifications.

SUBSURFACE EXPLORATION PROCEDURES

Test Borings

We performed 12 SPT borings on May 24, 2021 with a truck rig equipped with hollow-stem auger. Soil sampling was performed in accordance with the procedures described in ASTM:D1586. Using this procedure, a 2-inch O.D. split barrel sampler is driven into the soil by a 140-pound weight falling 30 inches. After an initial set of 6 inches, the number of blows required to drive the sampler an additional 12 inches is known as the penetration resistance, or “N” value. The “N” value is an index of the relative density of cohesionless soils and the consistency of cohesive soils. In addition, thin walled tube samples were obtained according to ASTM:D1587, where indicated by the appropriate symbol on the boring logs.

The test borings were backfilled with on-site materials and some settlement of these materials can be expected to occur. Final closure of the holes is the responsibility of the client or property owner.

The soil samples collected from the test boring locations will be retained in our office for a period of 1 month after the date of this report and will then be discarded unless we are notified otherwise.

Soil Classification

As the samples were obtained in the field, they were visually and manually classified by the crew chief according to ASTM:D2488. Representative portions of all samples were then sealed and returned to the laboratory for further examination and for verification of the field classification. In addition, select samples were then submitted to a program of laboratory tests. Where laboratory classification tests (sieve analysis and Atterberg limits) have been performed, classifications according to ASTM:D2487 are possible. Logs of the test borings indicating the depth and identification of the various strata, the “N” value, the laboratory test data, water level information and pertinent information regarding the method of maintaining and advancing the drill holes are also attached in Appendix A. Charts illustrating the soil classification procedures,

the descriptive terminology and the symbols used on the boring logs are also attached in Appendix A.

Water Level Measurements

Subsurface groundwater levels should be expected to fluctuate seasonally and yearly from the groundwater readings recorded at the test boring locations. Fluctuations occur due to varying seasonal and yearly rainfall amounts and snowmelt, as well as other factors. It is possible that the subsurface groundwater levels during or after construction could be significantly different than the time the test borings were performed.

Laboratory Tests

Laboratory tests were performed on select samples to aid in determining the index properties of the soils. The index tests consisted of moisture content, dry density, sieve analysis (#200 sieve wash) and unconfined compressive strength. The laboratory tests were performed in accordance with the appropriate ASTM procedures. The results of the laboratory tests are shown on the boring logs opposite the samples upon which the tests were performed or on the data sheets included in the Appendix.

LIMITATIONS

The recommendations and professional opinions submitted in this report were based upon the data obtained through the sampling and testing program at the test boring locations. We wish to point out that because no exploration program can totally reveal the exact subsurface conditions for the entire site, conditions between test borings and between samples and at other times may differ from those described in our report. Our exploration program identified subsurface conditions only at those points where samples were retrieved or where water was observed. It is not standard engineering practice to continuously retrieve samples for the full depth of the test borings. Therefore, strata boundaries and thicknesses must be inferred to some extent. Additionally, some soils layers present in the ground may not be observed between sampling intervals. If the subsurface conditions encountered at the time of construction differ from those represented by our test borings, it is necessary to contact us so that our recommendations can be


reviewed. The variations may result in altering our conclusions or recommendations regarding site preparation or construction procedures, thus, potentially affecting construction costs.

This report is for the exclusive use of the addressee and its representatives for use in design of the proposed project described herein and preparation of construction documents. Without written approval, we assume no responsibility to other parties regarding this report. Our conclusions, opinions and recommendations may not be appropriate for other parties or projects.


STANDARD OF CARE

The recommendations submitted in this report represent our professional opinions. Our services for your project were performed in a manner consistent with that level of care and skill ordinarily exercised by members of the engineering profession currently practicing at this time and area.

This report was prepared by:
GeoTek Engineering & Testing Services, Inc.



Jayden Waldner, EIT
Staff Engineer



Daniel R Hanson, PE
General Manager





FIGURE 1
SITE LOCATION MAP
PROPOSED SHEEP BARN/SHED
3RD STREET SW
HURON, SD
ACAD/GEOTEK/JAYDEN/24-0868

PROJECT#: 24-0868

DRAWN BY: MW



GEOTEK ENGINEERING & TESTING SERVICES, INC.
909 East 50th Street North
Sioux Falls, South Dakota 57104
605-335-5512 Fax 605-335-0773




FIGURE 2
 TEST BORING LOCATION MAP
 PROPOSED SHEEP BARN/SHED
 3RD STREET SW
 HURON, SD

ACAD/GEOTEK/JAYDEN/24-0868

PROJECT#: 24-0868

DRAWN BY: MW

GEOTEK

GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 East 50th Street North
 Sioux Falls, South Dakota 57104
 605-335-5512 Fax 605-335-0773



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # 24-0868

BORING NO. 1 (1 of 1)

PROJECT Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD

DEPTH in FEET	DESCRIPTION OF MATERIAL	GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS								
					NO.	TYPE	WC	D	LL	PL	QU				
	↓ SURFACE ELEVATION <u>98.2 ft</u>														
	FILL, MOSTLY LEAN CLAY WITH SAND: a trace of gravel, brown and black, moist, a 4" layer of asphalt and 3" of gravel at the surface	FILL			1	HSA	12								
4½			6		2	SPT	11	114							
	SILTY SAND: fine grained, brown and gray, moist to wet, loose, 13% passing the #200 sieve at 4.5' (SM)	MIXED ALLUVIUM	8		3	SPT	25								
			6	▼	4	SPT	24	103							
9½															
	SAND: a trace of gravel, fine to medium grained, brown, waterbearing, loose, (SP)	COARSE ALLUVIUM	8		5	SPT									
11															
	LEAN CLAY WITH SAND: a little gravel, dark gray, moist, firm to stiff, (CL)	GLACIAL TILL	7		6	SPT									
			8		7	SPT	13								
21			9		8	SPT									
	Bottom of borehole at 21 feet.														

GEOTECHNICAL TEST BORING - 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24

WATER LEVEL MEASUREMENTS

START 6-18-24 COMPLETE 6-18-24 11:10 am

DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD
6-18-24	11:10 am	21	--	7	▼ 7.0	3.25" ID Hollow Stem Auger
--	--	--	--	--	--	
--	--	--	--	--	--	
--	--	--	--	--	--	CREW CHIEF Roy Hanson



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # 24-0868

BORING NO. 2 (1 of 1)

PROJECT Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD

DEPTH in FEET	DESCRIPTION OF MATERIAL	GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS								
					NO.	TYPE	WC	D	LL	PL	QU				
	↓ SURFACE ELEVATION <u>97.7 ft</u>														
2	FILL, MOSTLY LEAN CLAY WITH SAND: black, moist, a 4" layer of asphalt and 4.5" of gravel at the surface	FILL			1	HSA	13								
	SANDY LEAN CLAY: light brown, moist, firm, (CL)	FINE ALLUVIUM	8		2	SPT	8								
4½	SILTY SAND: fine grained, brown and gray, moist to wet, medium dense, 41% passing the #200 wash sieve at 4.5' (SM)	MIXED ALLUVIUM	9		3	SPT	27								
7	SAND: a trace of gravel, fine to medium grained, brown, waterbearing, medium dense, 5% passing the #200 wash sieve at 7' (SP)	COARSE ALLUVIUM	9		4	SPT									
11	LEAN CLAY WITH SAND: a little gravel, dark gray, moist, stiff, a lens of sand above 15.5' (CL)	GLACIAL TILL	12		5	SPT									
			13		6	SPT	16	111							
			14		7	SPT	19	110							
16	Bottom of borehole at 16 feet.														

WATER LEVEL MEASUREMENTS

START 6-18-24 COMPLETE 6-18-24 3:10 pm

DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD
6-18-24	3:10 pm	16	--	11	6.0	3.25" ID Hollow Stem Auger
--	--	--	--	--	--	
--	--	--	--	--	--	
--	--	--	--	--	--	CREW CHIEF Roy Hanson

GEOTECHNICAL TEST BORING 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # 24-0868

BORING NO. 3 (1 of 1)

PROJECT Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD

DEPTH in FEET	DESCRIPTION OF MATERIAL	GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS									
					NO.	TYPE	WC	D	LL	PL	QU					
	↓ SURFACE ELEVATION <u>99.5 ft</u>															
	FILL, MOSTLY LEAN CLAY WITH SAND: a trace of gravel, brown and black, moist, a 7" layer of gravel at the surface	FILL			1	HSA	14									
4½			13		2	SPT	13	116								
	SAND WITH SILT: fine to medium grained, brown, moist, loose, 11% passing the #200 wash sieve at 4.5' (SP-SM)	COARSE ALLUVIUM	8		3	SPT	16									
7					4	SPT	23	104								2200
	LEAN CLAY WITH SAND: a little gravel, brown, moist, stiff, (CL)	GLACIAL TILL	9													
9½					5	SPT	21	106								
	LEAN CLAY WITH SAND: a little gravel, brown and dark brown, moist, stiff, (CL)	GLACIAL TILL	12													
13½			13		6	SPT										
	LEAN CLAY WITH SAND: a little gravel, dark gray, moist, stiff, (CL)	GLACIAL TILL	11		7	SPT										
16	Bottom of borehole at 16 feet.															

WATER LEVEL MEASUREMENTS

START 6-18-24 COMPLETE 6-18-24 11:45 am

DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD
6-18-24	11:45 am	16	--	14	None	3.25" ID Hollow Stem Auger
6-18-24	3:30 pm	16	--	11	▼ 9.5	
--	--	--	--	--	--	
--	--	--	--	--	--	CREW CHIEF Roy Hanson

GEOTECHNICAL TEST BORING 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # 24-0868

BORING NO. 4 (1 of 1)

PROJECT Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD

DEPTH in FEET	DESCRIPTION OF MATERIAL	GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS								
					NO.	TYPE	WC	D	LL	PL	QU				
	↓ SURFACE ELEVATION <u>98.3 ft</u>														
	FILL, MOSTLY LEAN CLAY WITH SAND: a trace of gravel, brown and black, moist, a 6" layer of gravel at the surface	FILL				1	HSA	12							
4½			12			2	SPT	12	118						
6	SAND: fine grained, brown, moist, loose, (SP)	COARSE ALLUVIUM	6			3	SPT	20							
	LEAN CLAY WITH SAND: a little gravel, brown and gray, moist, stiff, (CL)	GLACIAL TILL													
9½			9	▼		4	SPT	22	104						
	LEAN CLAY WITH SAND: a little gravel, dark brown, moist, stiff, (CL)	GLACIAL TILL	12			5	SPT	22	105						
			12			6	SPT	19	110						
14½															
	LEAN CLAY WITH SAND: a little gravel, dark gray, moist, firm to stiff, a lens of sand above 20.5' (CL)	GLACIAL TILL	7			7	SPT								
						8	SH								
21			12			9	SPT								
	Bottom of borehole at 21 feet.														

WATER LEVEL MEASUREMENTS

START 6-18-24 COMPLETE 6-18-24 2:25 pm

DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD
6-18-24	2:25 pm	21	--	19	None	3.25" ID Hollow Stem Auger
6-18-24	3:43 pm	21	--	18	▼ 8.1	
--	--	--	--	--	--	
--	--	--	--	--	--	CREW CHIEF Roy Hanson

GEOTECHNICAL TEST BORING 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # 24-0868

BORING NO. 5 (1 of 1)

PROJECT **Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD**

DEPTH in FEET	DESCRIPTION OF MATERIAL	GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS								
					NO.	TYPE	WC	D	LL	PL	QU				
	↓ SURFACE ELEVATION <u>99.3 ft</u>														
2	FILL, MOSTLY LEAN CLAY: brown and black, moist, a 7" layer of gravel at the surface	FILL			1	HSA	14								
	SANDY LEAN CLAY: dark brown, moist, firm, (CL)	FINE ALLUVIUM	6		2	SPT	14	112							
4½	SAND WITH SILT: fine grained, brown and gray, moist, loose, a lens of sand above 5' (SP-SM)	COARSE ALLUVIUM	6	▼	3	SPT	26								
6	LEAN CLAY WITH SAND: a little gravel, brown, moist to wet, stiff, (CL)	GLACIAL TILL			4	SPT	22	103							
			11		5	SPT	24	101							
			11		6	SPT									
14½	LEAN CLAY WITH SAND: a little gravel, dark gray, moist to wet, stiff, a lens of sand above 16' (CL)	GLACIAL TILL	12		7	SPT	19								
					8	SPT									
21	Bottom of borehole at 21 feet.		11												

GEOTECHNICAL TEST BORING 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24

WATER LEVEL MEASUREMENTS

START 6-18-24 COMPLETE 6-18-24 12:40 pm

DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD
6-18-24	12:40 pm	21	--	18	None	3.25" ID Hollow Stem Auger
6-18-24	3:35 pm	21	--	11	▼ 5.5	
--	--	--	--	--	--	
--	--	--	--	--	--	CREW CHIEF Roy Hanson



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # <u>24-0868</u>						BORING NO. <u>6 (1 of 1)</u>									
PROJECT <u>Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD</u>															
DEPTH in FEET	DESCRIPTION OF MATERIAL SURFACE ELEVATION <u>98.3 ft</u>				GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS					
								NO.	TYPE	WC	D	LL	PL	QU	
2	FILL, MOSTLY LEAN CLAY WITH SAND: black, moist, a 7" layer of gravel at the surface				FILL			1	HSA	13					
4	SANDY LEAN CLAY: dark brown, moist, firm, (CL)				FINE ALLUVIUM	6		2	SPT	27	102				
4 1/2	LEAN CLAY WITH SAND: a little gravel, brown and gray, moist, firm, (CL)				GLACIAL TILL	8		3	SPT	31	98				2000
9 1/2	LEAN CLAY WITH SAND: a little gravel, dark brown, moist, stiff, a lens of sand above 10.5' (CL)				GLACIAL TILL	14		4	SPT	23	103				
12	LEAN CLAY WITH SAND: a little gravel, dark gray, moist, stiff, (CL)				GLACIAL TILL	10		5	SPT	19	110				
16	LEAN CLAY WITH SAND: a little gravel, dark gray, moist, stiff, (CL)				GLACIAL TILL	10		6	SPT	16					
	Bottom of borehole at 16 feet.							7	SPT	20					
WATER LEVEL MEASUREMENTS						START <u>6-18-24</u> COMPLETE <u>6-18-24 1:40 pm</u>									
DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD									
6-18-24	1:40 pm	16	--	14	None	3.25" ID Hollow Stem Auger									
6-18-24	3:40 pm	16	--	10.5	7.3										
--	--	--	--	--	--										
--	--	--	--	--	--	CREW CHIEF Roy Hanson									

GEOTECHNICAL TEST BORING 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # <u>24-0868</u>						BORING NO. <u>7 (1 of 1)</u>									
PROJECT <u>Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD</u>															
DEPTH in FEET	DESCRIPTION OF MATERIAL SURFACE ELEVATION <u>98.8 ft</u>					GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS				
									NO.	TYPE	WC	D	LL	PL	QU
2	FILL, MOSTLY LEAN CLAY: a little gravel, brown and black, moist, a 5" layer of gravel at the surface					FILL	21		1	SPT	14	118			
4 1/2	LEAN CLAY WITH SAND: a trace of gravel, brown, moist, stiff, (CL)					GLACIAL TILL	11		2	SPT	17	113			
6	LEAN CLAY WITH SAND: a little gravel, gray, moist, stiff, (CL)					GLACIAL TILL	9		3	SPT	22	102			
Bottom of borehole at 6 feet.															
WATER LEVEL MEASUREMENTS						START <u>6-18-24</u> COMPLETE <u>6-18-24 12:55 pm</u>									
DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD									
6-18-24	12:55 pm	6	--	4	None	3.25" ID Hollow Stem Auger									
--	--	--	--	--	--										
--	--	--	--	--	--										
--	--	--	--	--	--	CREW CHIEF Roy Hanson									

GEOTECHNICAL TEST BORING 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24



GEOTEK ENGINEERING & TESTING SERVICES, INC.
 909 E 50th St. N
 Sioux Falls, SD 57104
 (605) 335-5512 Fax (605) 335-0773
 info@geotekeng.com

GEOTECHNICAL TEST BORING LOG

GEOTEK # <u>24-0868</u>						BORING NO. <u>8 (1 of 1)</u>								
PROJECT <u>Proposed Sheep Barn/SHED, State Fair Grounds, 3rd Street SW, Huron, SD</u>														
DEPTH in FEET	DESCRIPTION OF MATERIAL SURFACE ELEVATION <u>97.4 ft</u>				GEOLOGIC ORIGIN	N	WL	SAMPLE		LABORATORY TESTS				
								NO.	TYPE	WC	D	LL	PL	QU
2	FILL, MOSTLY LEAN CLAY WITH SAND: dark brown, moist, a 4" layer of asphalt and 4" of gravel at the surface				FILL	6		1	SPT	13	117			
4 1/2	SANDY LEAN CLAY: light brown, moist, firm, (CL)				FINE ALLUVIUM	6		2	SPT	15	111			
6	SAND WITH SILT: fine grained, brown, moist to wet, loose, (SP-SM)				COARSE ALLUVIUM	6		3	SPT	22				
Bottom of borehole at 6 feet.														
WATER LEVEL MEASUREMENTS						START	<u>6-18-24</u>		COMPLETE	<u>6-18-24 3:25 pm</u>				
DATE	TIME	SAMPLED DEPTH	CASING DEPTH	CAVE-IN DEPTH	WATER LEVEL	METHOD								
6-18-24	3:25 pm	6	--	4	None	6" Flight Auger								
--	--	--	--	--	--									
--	--	--	--	--	--									
--	--	--	--	--	--	CREW CHIEF Roy Hanson								

GEOTECHNICAL TEST BORING - 24-0868.GPJ GEOTEKENG2019.GDT 6/25/24

SOIL CLASSIFICATION CHART

MAJOR DIVISIONS			SYMBOLS		TYPICAL DESCRIPTIONS	
			GRAPH	LETTER		
<p>COARSE GRAINED SOILS</p> <p>MORE THAN 50% OF MATERIAL IS LARGER THAN NO. 200 SIEVE SIZE</p>	<p>GRAVEL AND GRAVELLY SOILS</p>	<p>CLEAN GRAVELS</p> <p>(LITTLE OR NO FINES)</p>		GW	WELL-GRADED GRAVELS, GRAVEL - SAND MIXTURES, LITTLE OR NO FINES	
		<p>GRAVELS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		GP	POORLY-GRADED GRAVELS, GRAVEL - SAND MIXTURES, LITTLE OR NO FINES	
		<p>GRAVELS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		GM	SILTY GRAVELS, GRAVEL - SAND - SILT MIXTURES	
		<p>GRAVELS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		GC	CLAYEY GRAVELS, GRAVEL - SAND - CLAY MIXTURES	
	<p>SAND AND SANDY SOILS</p>	<p>CLEAN SANDS</p> <p>(LITTLE OR NO FINES)</p>		SW	WELL-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES	
		<p>CLEAN SANDS</p> <p>(LITTLE OR NO FINES)</p>		SP	POORLY-GRADED SANDS, GRAVELLY SAND, LITTLE OR NO FINES	
		<p>SANDS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		SM	SILTY SANDS, SAND - SILT MIXTURES	
		<p>SANDS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		SC	CLAYEY SANDS, SAND - CLAY MIXTURES	
		<p>FINE GRAINED SOILS</p> <p>MORE THAN 50% OF MATERIAL IS SMALLER THAN NO. 200 SIEVE SIZE</p>	<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT LESS THAN 50</p>		ML	INORGANIC SILTS AND VERY FINE SANDS, ROCK FLOUR, SILTY OR CLAYEY FINE SANDS OR CLAYEY SILTS WITH SLIGHT PLASTICITY
					CL	INORGANIC CLAYS OF LOW TO MEDIUM PLASTICITY, GRAVELLY CLAYS, SANDY CLAYS, SILTY CLAYS, LEAN CLAYS
	OL			ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY		
<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT GREATER THAN 50</p>			MH	INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS FINE SAND OR SILTY SOILS		
			CH	INORGANIC CLAYS OF HIGH PLASTICITY		
<p>HIGHLY ORGANIC SOILS</p>				OH	ORGANIC CLAYS OF MEDIUM TO HIGH PLASTICITY, ORGANIC SILTS	
<p>HIGHLY ORGANIC SOILS</p>				PT	PEAT, HUMUS, SWAMP SOILS WITH HIGH ORGANIC CONTENTS	

NOTE: DUAL SYMBOLS ARE USED TO INDICATE BORDERLINE SOIL CLASSIFICATIONS

BORING LOG SYMBOLS AND DESCRIPTIVE TERMINOLOGY

SYMBOLS FOR DRILLING AND SAMPLING

<u>Symbol</u>	<u>Definition</u>
Bag	Bag sample
CS	Continuous split-spoon sampling
DM	Drilling mud
FA	Flight auger; number indicates outside diameter in inches
HA	Hand auger; number indicates outside diameter in inches
HSA	Hollow stem auger; number indicates inside diameter in inches
LS	Liner sample; number indicates outside diameter of liner sample
N	Standard penetration resistance (N-value) in blows per foot
NMR	No water level measurement recorded, primarily due to presence of drilling fluid
NSR	No sample retrieved; classification is based on action of drilling equipment and/or material noted in drilling fluid or on sampling bit
SH	Shelby tube sample; 3-inch outside diameter
SPT	Standard penetration test (N-value) using standard split-spoon sampler
SS	Split-spoon sample; 2-inch outside diameter unless otherwise noted
WL	Water level directly measured in boring
▼	Water level symbol

SYMBOLS FOR LABORATORY TESTS

<u>Symbol</u>	<u>Definition</u>
WC	Water content, percent of dry weight; ASTM:D2216
D	Dry density, pounds per cubic foot
LL	Liquid limit; ASTM:D4318
PL	Plastic limit; ASTM:D4318
QU	Unconfined compressive strength, pounds per square foot; ASTM:D2166

DENSITY/CONSISTENCY TERMINOLOGY

<u>Density</u>	<u>Consistency</u>	
<u>Term</u>	<u>N-Value</u>	<u>Term</u>
Very Loose	0-4	Soft
Loose	5-8	Firm
Medium Dense	9-15	Stiff
Dense	16-30	Very Stiff
Very Dense	Over 30	Hard

PARTICLE SIZES

<u>Term</u>	<u>Particle Size</u>
Boulder	Over 12"
Cobble	3" – 12"
Gravel	#4 – 3"
Coarse Sand	#10 – #4
Medium Sand	#40 – #10
Fine Sand	#200 – #40
Silt and Clay	passes #200 sieve

DESCRIPTIVE TERMINOLOGY

<u>Term</u>	<u>Definition</u>
Dry	Absence of moisture, powdery
Frozen	Frozen soil
Moist	Damp, below saturation
Waterbearing	Pervious soil below water
Wet	Saturated, above liquid limit
Lamination	Up to ½" thick stratum
Layer	½" to 6" thick stratum
Lens	½" to 6" discontinuous stratum

GRAVEL PERCENTAGES

<u>Term</u>	<u>Range</u>
A trace of gravel	2-4%
A little gravel	5-15%
With gravel	16-50%

THIS PAGE INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

PROCUREMENT AND CONTRACTING REQUIREMENTS GROUP

DIVISION 00 – PROCUREMENT AND CONTRACTING REQUIREMENTS

00 01 10	TABLE OF CONTENTS
<u>00 31 32</u>	<u>GEOTECHNICAL DATA</u>
<u>00 91 13</u>	<u>ADDENDA</u>

DIVISION 01 – GENERAL REQUIREMENTS

01 23 00	ALTERNATES
----------	------------

SPECIFICATIONS GROUP

FACILITY CONSTRUCTION SUBGROUP

(Note: Sections marked (S) prepared by Structural consultant)

DIVISION 02 - EXISTING CONDITIONS

02 41 19	SELECTIVE DEMOLITION
----------	----------------------

DIVISION 03 - CONCRETE

03 10 00	CONCRETE FORMING AND ACCESSORIES (S)
03 20 00	CONCRETE REINFORCING (S)
03 30 00	CAST-IN-PLACE CONCRETE (S)
03 35 43	POLISHED CONCRETE FINISHING

DIVISION 04 - MASONRY

04 26 13	MASONRY VENEER
----------	----------------

DIVISION 05 - METALS

05 12 00	STRUCTURAL STEEL FRAMING (S)
05 52 13	PIPE AND TUBE RAILINGS

DIVISION 06 - WOOD, PLASTICS, AND COMPOSITES

06 10 00	ROUGH CARPENTRY (S)
06 10 53	MISCELLANEOUS ROUGH CARPENTRY
06 16 00	SHEATHING (S)
06 17 15	ENGINEERED STRUCTURAL WOOD (S)
06 17 53	SHOP-FABRICATED WOOD TRUSSES (S)
06 18 00	GLUED-LAMINATED CONSTRUCTION (S)
06 20 13	EXTERIOR FINISH CARPENTRY
06 20 23	INTERIOR FINISH CARPENTRY
<u>06 61 13</u>	<u>SIMULATED STONE FABRICATIONS</u>

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

07 21 00 THERMAL INSULATION
07 25 00 WEATHER BARRIERS
07 26 00 VAPOR RETARDERS
07 41 13.13 FORMED METAL ROOF PANELS
07 42 13.13 FORMED METAL WALL PANELS
07 72 53 SNOW GUARDS
07 92 00 JOINT SEALANTS

DIVISION 08 - OPENINGS

08 11 13 HOLLOW METAL DOORS AND FRAMES
08 36 13 SECTIONAL DOORS
08 43 13 ALUMINUM-FRAMED STOREFRONTS
08 51 13 ALUMINUM WINDOWS
08 71 00 DOOR HARDWARE
08 80 00 GLAZING

DIVISION 09 - FINISHES

09 29 00 GYPSUM BOARD
09 51 23 ACOUSTICAL TILE CEILINGS
09 65 13 RESILIENT BASE AND ACCESSORIES
09 65 19 RESILIENT TILE FLOORING
09 67 23 RESINOUS FLOORING
09 91 13 EXTERIOR PAINTING
09 91 23 INTERIOR PAINTING

DIVISION 10 - SPECIALTIES

10 14 23.16 ROOM-IDENTIFICATION PANEL SIGNAGE
10 21 13.19 PLASTIC TOILET COMPARTMENTS
10 26 00 WALL AND DOOR PROTECTION
10 28 00 TOILET, BATH, AND LAUNDRY ACCESSORIES
10 44 13 FIRE PROTECTION CABINETS
10 44 16 FIRE EXTINGUISHERS

DIVISION 12 - FURNISHINGS

12 36 23.13 PLASTIC-LAMINATE-CLAD COUNTERTOPS

FACILITY SERVICES SUBGROUP

DIVISION 22 - PLUMBING

SEE DRAWINGS FOR PLUMBING SPECIFICATIONS

DIVISION 23 – HEATING, VENTILATION, AND AIR CONDITIONING (HVAC)

SEE DRAWINGS FOR HVAC SPECIFICATIONS

DIVISION 26 - ELECTRICAL

26 00 10	SUPPLEMENTAL REQUIREMENTS FOR ELECTRICAL
26 05 19	LOW-VOLTAGE ELECTRICAL POWER CONDUCTORS AND CABLES
26 05 26	GROUNDING AND BONDING FOR ELECTRICAL SYSTEMS
26 05 29	HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS
26 05 33.13	CONDUITS FOR ELECTRICAL SYSTEMS
26 05 33.16	BOXES AND COVERS FOR ELECTRICAL SYSTEMS
26 05 44	SLEEVES AND SLEEVE SEALS FOR ELECTRICAL RACEWAYS AND CABLING
26 05 53	IDENTIFICATION FOR ELECTRICAL SYSTEMS
26 05 73	POWER SYSTEM STUDIES
26 09 23	LIGHTING CONTROL DEVICES
26 24 16	PANELBOARDS
26 27 26	WIRING DEVICES
26 50 00	LIGHTING

DIVISION 27 - COMMUNICATIONS

27 05 28	PATHWAYS FOR COMMUNICATIONS SYSTEMS
----------	-------------------------------------

DIVISIONS 31-33 - EARTHWORK, EXTERIOR IMPROVEMENTS, UTILITIES

SEE DRAWINGS FOR EARTHWORK, EXTERIOR IMPROVEMENTS, AND UTILITIES SPECIFICATIONS.

<u>32 33 00</u>	<u>SITE FURNISHINGS (PROVIDED BY THE ARCHITECT)</u>
-----------------	---

END OF TABLE OF CONTENTS

THIS PAGE INTENTIONALLY LEFT BLANK

**DOCUMENT 009113
ADDENDA**

PART 1 - GENERAL

1.1 ADDENDUM

- A. Addendum No. 2.

1.2 REVISIONS TO DIVISION 00 PROCUREMENT REQUIREMENTS AND CONTRACTING REQUIREMENTS

- A. Document 000110 "Table of Contents," (reissued).
 - 1. Updated to include added sections.
- B. Document 003132 "Geotechnical Data," (new).
 - 1. Includes geotechnical report and soil boring data appended to section.

1.3 REVISIONS TO DIVISION 01 GENERAL REQUIREMENTS

- A. Specification Section 012300 "Alternates," (not reissued).
 - 1. Paragraph 3.1 Schedule of Alternates: Bid Alternate No. 3 (Wash Bay Reduction) is the only portion of the project where DARPA funding is applied and subject to the additional requirements.

1.4 REVISIONS TO DIVISIONS 02 - 49 SPECIFICATION SECTIONS

- A. Specification Section 062013 "Exterior Finish Carpentry," (not reissued).
 - 1. Paragraph 2.1 Exterior Trim (TR-2): Replace Fiber-Cement Trim with Lumber for Opaque Finish (Painted Finish).
 - a. Species and Grade: Any hardwood species suitable for exterior exposure.
 - b. Finger Jointing: Not allowed.
 - c. Face Surface: Surfaced (smooth).
 - d. Priming: Factory- or site-primed with primer compatible with paint in Section 099113 "Exterior Painting."
- B. Specification Section 066113 "Simulated Stone Fabrications," (new).
 - 1. New section added for solid surface window stools.

- C. Specification Section 096519 "Resilient Tile Flooring," (not reissued).
 - 1. Paragraph 2.2 Vinyl Composition Floor Tile (LVT-1): Add clarification to use interlocking floating LVT.
 - 2. Paragraph 2.3 Installation Materials: Remove "adhesives" subparagraph.
- D. Specification Section 101423.16 "Room-Identification Panel Signage," (new).
 - 1. New section added for signage.
- E. Specification Section 102600 "Wall and Door Protection," (not reissued).
 - 1. Paragraph 2.4 Abuse-Resistant Wall Coverings: Add basis-of-design Crane Composites; Sequentia Fiberglass Reinforced Wall Panels (FRP).
- F. Specification Section 102800 "Toilet, Bath, and Laundry Accessories," (not reissued).
 - 1. Paragraph 1.6 Warranty:
 - a. Manufacturer's Special Warranty for Mirrors: 15-year warranty period.
 - b. Manufacturer's Special Warranty for Hand Dryers: 5-year warranty period.
 - 2. Paragraph 2.2 Public-Use Washroom Accessories: Addition of Toilet Tissue (Jumbo-Roll) Dispenser.
 - a. Description: Two-roll unit with sliding panel to expose other roll.
 - b. Mounting: Surface mounted.
 - c. Capacity: 9- or 10-inch-diameter rolls.
 - d. Material and Finish: ABS plastic, gray, with translucent front cover.
 - e. Lockset: Tumbler type.
 - f. Refill Indicator: Pierced slots at front.
- G. Specification Section 323300 "Site Furnishings," (new).
 - 1. New section added for concrete-filled steel pipe bollards (section provided by the Architect).

PART 2 - PRODUCTS (Not Used)
PART 3 - EXECUTION (Not Used)

END OF DOCUMENT 009113

**SECTION 066116
SIMULATED STONE FABRICATIONS**

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Solid surface material window stools.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of solid surface material.
- B. Shop Drawings:
 - 1. Plans, sections, details, and attachment to other work.
 - 2. Direction of directional pattern, if any.
- C. Samples for Initial Selection: For each type of material exposed to view.

1.3 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For solid surface material fabrications to include in maintenance manuals. Include product data for care products used or recommended by Installer and names, addresses, and telephone numbers of local sources for products.

1.4 DELIVERY, STORAGE, AND HANDLING

- A. Deliver fabrications only after casework and supports on which they will be installed have been completed in installation areas.
- B. Store fabrications in areas where environmental conditions comply with requirements specified in "Field Conditions" Article.
- C. Keep surfaces of fabrications covered with protective covering during handling and installation.

1.5 FIELD CONDITIONS

- A. Field Measurements: Where fabrications are indicated to fit to other construction, verify dimensions of fabrications by field measurements before countertop fabrication is complete and indicate measurements on Shop Drawings. Coordinate fabrication schedule with construction progress to avoid delaying the Work..

PART 2 - PRODUCTS

2.1 SOLID SURFACE MATERIALS

- A. Solid Surface Material: Homogeneous fabrication of mineral fillers and pigments bound together with a matrix of polymers and resins, complying with ISFA 2-01.
- B. Window Stools: Fabricate window stools equal to the width of the window opening and depth allowing a ½-inch overhang. Pre-fabricated window stools are allowed.
 - 1. Colors and Patterns: As selected by Architect from manufacturer's full range.
 - 2. Type: Standard.
 - 3. Thickness: 1/2-inch- thick, solid surface material.
 - 4. Exposed Edge Treatment: Radius.

2.2 FABRICATION

- A. Fabricate in sizes and shapes required to comply with requirements indicated.
- B. Fabricate with shop-applied edges unless otherwise indicated. Comply with solid surface material manufacturer's written instructions for adhesives, sealers, fabrication, and finishing.
- C. Joints: Fabricate without joints.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates to receive fabrications and conditions under which fabrications will be installed, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of fabrications.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Before installation, condition fabrications to average prevailing humidity conditions in installation areas.
- B. Examine shop-fabricated work for completion and complete work as required, including removal of packing.

3.3 INSTALLATION OF SIMULATED STONE FABRICATIONS

- A. Grade: Install fabrications to comply with specified grade.

- B. Assemble fabrications and complete fabrication at Project site to the extent that it was not completed in the shop.
- C. Window Stools Installation:
 - 1. Scribe and cut window stools to fit adjoining work, refinish cut surfaces, and repair damaged finish at cuts.
 - 2. Install window stools level to a tolerance of 1/8 inch maximum.
 - 3. Secure window stools with adhesive according to manufacturer's written instructions.
 - 4. Seal joints where window stools abut walls and window frames. Comply with Section 079200 "Joint Sealants."

3.4 ADJUSTING AND CLEANING

- A. Repair damaged and defective fabrications, where possible, to eliminate functional and visual defects. Where not possible to repair, replace fabrications. Adjust joinery for uniform appearance.
- B. Clean fabrications on exposed and semi-exposed surfaces.
- C. Protection: Provide Kraft paper or other suitable covering over simulated stone surfaces, taped to underside of fabrications. Remove protection at Substantial Completion.

END OF SECTION 123661

THIS PAGE INTENTIONALLY LEFT BLANK

SECTION 101423.16
ROOM-IDENTIFICATION PANEL SIGNAGE

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes room-identification signs that are directly attached to the building.

1.2 DEFINITIONS

- A. Accessible: In accordance with the accessibility standard.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings: For room-identification signs.
 - 1. Include fabrication and installation details and attachments to other work.
 - 2. Show sign mounting heights, locations of supplementary supports to be provided by other installers, and accessories.
 - 3. Show message list, typestyles, graphic elements, including raised characters and Braille, and layout for each sign at least half size.
- C. Samples for Initial Selection: For each type of sign assembly, exposed component, and exposed finish.
 - 1. Include representative Samples of available typestyles and graphic symbols.
- D. Product Schedule: For room-identification signs. Use same designations indicated on Drawings or specified.

1.4 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For signs to include in maintenance manuals.

1.5 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Variable Component Materials: 3 replaceable text inserts and interchangeable characters (letters, numbers, and graphic elements) of each type.
 - 2. Tools: One set(s) of specialty tools for assembling signs and replacing variable

sign components.

1.6 WARRANTY

- A. Special Warranty: Manufacturer agrees to repair or replace components of signs that fail in materials or workmanship within specified warranty period.
 - 1. Failures include, but are not limited to, the following:
 - a. Deterioration of finishes beyond normal weathering.
 - b. Deterioration of embedded graphic image.
 - c. Separation or delamination of sheet materials and components.
 - 2. Warranty Period: Five years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Accessibility Standard: Comply with applicable provisions in the USDOJ's "2010 ADA Standards for Accessible Design" and ICC A117.1.

2.2 ROOM-IDENTIFICATION SIGNS

- A. Room-Identification Sign: Sign with smooth, uniform surfaces; with message and characters having uniform faces, sharp corners, and precisely formed lines and profiles; and as follows:
 - 1. Laminated-Sheet Sign: Photopolymer face sheet with raised graphics laminated to acrylic or phenolic backing sheet to produce composite sheet.
 - a. Composite-Sheet Thickness: Manufacturer's standard for size of sign.
 - b. Surface-Applied Graphics: Applied vinyl film.
 - c. Color(s): As selected by Architect from manufacturer's full range.
 - 2. Sign-Panel Perimeter: Finish edges smooth.
 - a. Edge Condition: Beveled.
 - b. Corner Condition in Elevation: Rounded to manufacturer's standard radius.
 - 3. Mounting: Manufacturer's standard method for substrates indicated with adhesive or two-face tape.
 - 4. Text and Typeface: Accessible raised characters and Braille. Finish raised characters to contrast with background color, and finish Braille to match background color.

2.3 SIGN MATERIALS

- A. Acrylic Sheet: ASTM D4802, category as standard with manufacturer for each sign, Type UVF (UV filtering).
- B. Vinyl Film: UV-resistant vinyl film with pressure-sensitive, permanent adhesive; die cut to form characters or images as indicated on Drawings and suitable for exterior applications.
- C. Paints and Coatings for Sheet Materials: Inks, dyes, and paints that are recommended by manufacturer for optimum adherence to surface and are UV and water resistant for colors and exposure indicated.

2.4 ACCESSORIES

- A. Adhesive: As recommended by sign manufacturer.
- B. Two-Face Tape: Manufacturer's standard high-bond, foam-core tape, 0.045 inch thick, with adhesive on both sides.

2.5 FABRICATION

- A. General: Provide manufacturer's standard sign assemblies according to requirements indicated.
 - 1. Preassemble signs and assemblies in the shop to greatest extent possible. Disassemble signs and assemblies only as necessary for shipping and handling limitations. Clearly mark units for reassembly and installation; apply markings in locations concealed from view after final assembly.
 - 2. Mill joints to a tight, hairline fit. Form assemblies and joints exposed to weather to resist water penetration and retention.
 - 3. Conceal connections if possible; otherwise, locate connections where they are inconspicuous.
 - 4. Provide rabbets, lugs, and tabs necessary to assemble components and to attach to existing work. Drill and tap for required fasteners. Use concealed fasteners where possible; use exposed fasteners that match sign finish.
- B. Subsurface-Etched Graphics: Reverse etch back face of clear face-sheet material. Fill resulting copy with manufacturer's standard enamel. Apply opaque manufacturer's standard background color coating over enamel-filled copy.

2.6 GENERAL FINISH REQUIREMENTS

- A. Protect mechanical finishes on exposed surfaces from damage by applying a strippable, temporary protective covering before shipping.
- B. Appearance of Finished Work: Noticeable variations in same piece are not acceptable. Variations in appearance of adjoining components are acceptable if they are within the range of approved Samples and are assembled or installed to minimize contrast.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. General: Install signs using mounting methods indicated and according to manufacturer's written instructions.
 - 1. Install signs level, plumb, true to line, and at locations and heights indicated, with sign surfaces free of distortion and other defects in appearance.
 - 2. Install signs so they do not protrude or obstruct according to the accessibility standard.
 - 3. Before installation, verify that sign surfaces are clean and free of materials or debris that would impair installation.
- B. Accessibility: Install signs in locations on walls according to the accessibility standard.
- C. Mounting Methods:
 - 1. Adhesive: Clean bond-breaking materials from substrate surface and remove loose debris. Apply linear beads or spots of adhesive symmetrically to back of sign and of suitable quantity to support weight of sign after cure without slippage. Keep adhesive away from edges to prevent adhesive extrusion as sign is applied and to prevent visibility of cured adhesive at sign edges. Place sign in position, and push to engage adhesive. Temporarily support sign in position until adhesive fully sets.
 - 2. Two-Face Tape: Clean bond-breaking materials from substrate surface and remove loose debris. Apply tape strips symmetrically to back of sign and of suitable quantity to support weight of sign without slippage. Keep strips away from edges to prevent visibility at sign edges. Place sign in position, and push to engage tape adhesive.

3.2 ADJUSTING AND CLEANING

- A. Remove and replace damaged or deformed signs and signs that do not comply with specified requirements. Replace signs with damaged or deteriorated finishes or components that cannot be successfully repaired by finish touchup or similar minor repair procedures.
- B. Remove temporary protective coverings and strippable films as signs are installed.
- C. On completion of installation, clean exposed surfaces of signs according to manufacturer's written instructions, and touch up minor nicks and abrasions in finish. Maintain signs in a clean condition during construction and protect from damage until acceptance by Owner.

END OF SECTION 101423.16

**SECTION 323300
SITE FURNISHINGS**

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes: Bollards.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.

1.3 CLOSEOUT SUBMITTALS

- A. Maintenance Data: For site furnishings to include in maintenance manuals.

PART 2 - PRODUCTS

2.1 BOLLARDS

- A. Bollard Construction:
 - 1. Pipe OD: Not less than 4-1/2 inches.
 - a. Steel: Schedule 40 pipe.
 - 2. Style: Dome top.
 - 3. Overall Height: As indicated.
 - 4. Installation Method: As indicated.
- B. Steel Finish: Factory primed with manufacturer's standard zinc-rich, inorganic primer.
 - 1. Color: Safety Yellow.
 - 2. Topcoats: Manufacturer recommended zinc-rich, organic finish as needed.

2.2 MATERIALS

- A. Steel and Iron: Free of surface blemishes and complying with the following:
 - 1. Steel Pipe: Standard-weight steel pipe complying with ASTM A53/A53M, or electric-resistance-welded pipe complying with ASTM A135/A135M.

2.3 FABRICATION

- A. Metal Components: Form to required shapes and sizes with true, consistent curves, lines, and angles. Separate metals from dissimilar materials to prevent electrolytic action.
- B. Pipes and Tubes: Form simple and compound curves by bending members in jigs to produce uniform curvature for each repetitive configuration required; maintain cylindrical cross section of member throughout entire bend without buckling, twisting, cracking, or otherwise deforming exposed surfaces of handrail and railing components.
- C. Exposed Surfaces: Polished, sanded, or otherwise finished; all surfaces smooth, free of burrs, barbs, splinters, and sharpness; all edges and ends rolled, rounded, or capped.

2.4 GENERAL FINISH REQUIREMENTS

- A. Appearance of Finished Work: Noticeable variations in same piece are unacceptable. Variations in appearance of adjoining components are acceptable if they are within the range of approved Samples and are assembled or installed to minimize contrast.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine areas and conditions, with Installer present, for compliance with requirements for correct and level finished grade, mounting surfaces, installation tolerances, and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION






- A. Comply with manufacturer's written installation instructions unless more stringent requirements are indicated. Complete field assembly of site furnishings where required.
- B. Post Setting: Set cast-in support posts in concrete footing with smooth top, shaped to shed water. Protect portion of posts above footing from concrete splatter. Verify that posts are set plumb or at correct angle and are aligned and at correct height and spacing. Hold posts in position during placement and finishing operations until concrete is sufficiently cured.

END OF SECTION 323300


ESTIMATE OF QUANTITIES (BASE BID)			
ITEM	DESCRIPTION	QTY	UNIT
General Items			
1	Mobilization	1	LS
Removals			
2	Remove Gravel Surfacing	52,000	SF
3	Remove Asphalt Surfacing	19,050	SF
4	Sawcut Asphalt	125	LF
5	Remove Concrete Surfacing	455	SF
6	Remove Curb & Gutter	30	LF
Erosion Control			
7	F&I Temporary Vehicle Tracking Control	1	EA
8	F&I Concrete Washout Area	1	EA
9	F&I Sediment Control at Inlets w/Frames & Grates	10	EA
Water Main			
10	F&I 2" Domestic Water Service	112	LF
11	F&I 2" Curb Stop in Traffic Rated Collar	1	EA
12	Connect to Existing Water Main	1	EA
Sanitary Sewer			
13	F&I 6" Sanitary Sewer Service	156	LF
14	Connect to Existing Sanitary Sewer	1	EA
15	F&I 6" Sanitary Sewer Cleanout	1	EA
Surfacing			
16	F&I 10' Gravel Apron	7,180	SF
17	F&I Concrete Sidewalk	820	SF
18	F&I Gravel Surfacing	42,905	SF
19	F&I Concrete Curb & Gutter	30	LF
20	F&I Detectable Warning Panel	10	SF
Building Relocation			
21	Incidental Work - Grading	1	LS
22	F&I Contractor Furnished Borrow	30	CY
23	F&I Gravel Base Course	150	TON
24	Remove & Reset Chain Link Fence	150	LF

ESTIMATE OF QUANTITIES (ALTERNATE #2)			
ITEM	DESCRIPTION	QTY	UNIT
Surfacing			
1	F&I 10' Concrete Apron	7,180	SF

ESTIMATE OF QUANTITIES (ALTERNATE #3)			
ITEM	DESCRIPTION	QTY	UNIT
Removals			
1	Remove Railing w/Water	355	LF
2	Remove Concrete Wash Bay	3,865	SF
Utilities			
3	Adjust Storm Sewer Inlet Elevation	1	EA
4	F&I 1-1/2" Domestic Water Service	193	LF
Surfacing			
5	F&I Concrete Wash Bay	1,500	SF



Architecture | Planning | Interiors
434 5th St Suite 1
Brookings, SD 57006 | P: 605.692.4008
2301 W Russell St
Sioux Falls, SD 57104 | P: 605.692.4008



STAMP: 8/7/2024
Addendum #2

QUANTITIES & DETAILS

SHEET NAME: PROJECT NO. OSE#: M2319-10X

LIVESTOCK PLAZA/SHEEP BARN
HURON, SD

PROJECT MANAGER: NICK KUMMER
DATE: 07.17.2024

SHEET: C3.1

FOR CONSTRUCTION




Architecture | Planning | Interiors

434 5th St Suite 1
Brookings, SD 57006 | P: 605.692.4008

2301 W Russell St
Sioux Falls, SD 57104 | P: 605.692.4008



STAMP:



8/17/2024

1 Addendum #2

DEMOLITION PLAN

PROJECT NO:
OSE#: M2319-10X

LIVESTOCK
PLAZA/SHEEP BARN


HURON, SD

PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024

SHEET:

C4.1



Removal Legend			
Keynote		Description	Quantity
1		Remove Gravel Surfacing	52,000 SF
2		Remove Asphalt Surfacing	19,050 SF
3		Sawcut Asphalt	125 LF
4		Remove Concrete Surfacing	455 SF
5		Remove Curb & Gutter	30 LF

Removal Legend (Alternate #3)			
Keynote		Description	Quantity
3-1		Remove Railing w/Water	355 LF
3-2		Remove Concrete Wash Bay	3,865 SF

FOR CONSTRUCTION

DATE PRINTED: 7/16/2024 9:10:01 AM

FULL SCALE: 22x34
HALF SCALE: 11x17
DRAWING MAY NOT BE
PRINTED TO SCALE



Architecture | Planning | Interiors


434 5th St Suite 1
Brookings, SD 57006 | P: 605.692.4008

2301 W Russell St
Sioux Falls, SD 57104 | P: 605.692.4008



3314 Milwaukee Avenue NE
Suite 2
Aberdeen, SD 57401
PH: 605.225.3494
www.imegcorp.com

STAMP:



8/17/2024

Revisions:
1 Addendum #2

SITE GRADING & UTILITIES

PROJECT NO:
OSE#: M2319-10X


LIVESTOCK PLAZA/SHEEP BARN
HURON, SD

PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024

SHEET:

C5.1



Surfacing Legend		
Keynote	Description	Quantity
1	F&I 10' Gravel Apron	7,180 SF
2	F&I Concrete Sidewalk	820 SF
3	F&I Gravel Surfacing	42,905 SF
4	F&I Concrete Curb & Gutter	30 LF
5	F&I Detectable Warning Panel	10 SF
6	Landscaping (By Others)	2,435 SF





Surfacing Legend (Alternate #2)		
Keynote	Description	Quantity
2-1	F&I 10' Concrete Apron	7,180 SF

Surfacing Legend (Alternate #3)		
Keynote	Description	Quantity
3-1	F&I Concrete Wash Bay	1,500 SF

FOR CONSTRUCTION

DATE PRINTED: 7/16/2024 9:10:01 AM


FULL SCALE: 22x34
HALF SCALE: 11x17
DRAWING MAY NOT BE
PRINTED TO SCALE



Architecture | Planning | Interiors

434 5th St Suite 1
Brookings, SD 57006 | P: 605.692.4008

2301 W Russell St
Sioux Falls, SD 57104 | P: 605.692.4008



REVISIONS:	8/7/2024
1	Addendum #2

SHEET NAME:
BUILDING RELOCATION SITE PLAN

FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO.
OSE#: M2319-10X

LIVESTOCK PLAZA/SHEEP BARN

HURON, SD

PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024

SHEET:
R-C1.1


FOR CONSTRUCTION



ARCHITECTURE & ENGINEERING

Located in Sioux Falls, Brookings & Mitchell South Dakota

designargroup.com 605.692.4008



REVISIONS:	DATE:
NO. DESCRIPTION:	

SHEET NAME:
WALL & ASSEMBLY TYPES

FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO.
OSE#: M2319-10X
SD STATE FAIR

LIVESTOCK PLAZA/SHEEP BARN

HURON, SD

PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024

SHEET:

T1.3

A1. PARTITION WALL

NO RATING REQ'D.

- 5/8" MOISTURE RESISTANT GYP.
- 2x4 WOOD STUDS @ 16" O.C.
- SOUND ATTENUATION BATT INSUL.
- 5/8" MOISTURE RESISTANT GYP.

A2. PARTITION WALL

NO RATING REQ'D. STC **

- 5/8" MOISTURE RESISTANT GYP.
- 2x6 WOOD STUDS @ 16" O.C.
- SOUND ATTENUATION BATT INSUL.
- 5/8" MOISTURE RESISTANT GYP.

A3. CHASE WALL

NO RATING REQ'D. STC **

- 5/8" MOISTURE RESISTANT GYP.
- 2x8 WOOD STUDS @ 16" O.C.
- SOUND ATTENUATION BATT INSUL.
- 5/8" MOISTURE RESISTANT GYP.

E1. EXTERIOR WALL

NO RATING REQ'D.

- 2x8 WOOD STUDS (SEE STRUCT.)
- EXTERIOR SHEATHING (SEE STRUCT.)
- CONT. INFILTRATION BARRIER
- METAL PANEL. (SEE ELEV.)

E2. EXTERIOR WALL

NO RATING REQ'D.

- 2x8 WOOD STUDS (SEE STRUCT.)
- EXTERIOR SHEATHING (SEE STRUCT.)
- CONT. INFILTRATION BARRIER
- 1" AIR SPACE
- 4" SPLIT-FACE CMU

E3. EXTERIOR WALL

NO RATING REQ'D.

- 5/8" MOISTURE RESISTANT GYP.
- 6 MIL. CONTINUOUS VAPOR BARRIER
- FABRIC/NETTING FOR BLOWN-IN INSUL.
- 2x6 WOOD STUDS @ 16" O.C.
- MIN R-21 BLOWN-IN INSUL. SYSTEM.
- EXTERIOR SHEATHING (SEE STRUCT.)
- CONT. INFILTRATION BARRIER
- 1" AIR SPACE
- METAL LINER PANEL. (SEE ELEV.)

E4. EXTERIOR WALL

NO RATING REQ'D.

- 5/8" MOISTURE RESISTANT GYP.
- 6 MIL. CONTINUOUS VAPOR BARRIER
- FABRIC/NETTING FOR BLOWN-IN INSUL.
- 2x6 WOOD STUDS @ 16" O.C.
- MIN R-21 BLOWN-IN INSUL. SYSTEM.
- EXTERIOR SHEATHING (SEE STRUCT.)
- CONT. INFILTRATION BARRIER
- 1" AIR SPACE
- 4" SPLIT-FACE CMU

1 WALL TYPES
1 1/2" = 1'-0"

2 ASSEMBLY TYPES
1" = 1'-0"

ELEVATION

ACCESSIBLE URINAL

PLAN

AMBULATORY ACCESSIBLE WATER CLOSET

PLAN

WHEELCHAIR ACCESSIBLE WATER CLOSET

ELEVATION

TOILET SEAT, GRAB BAR & DISPENSER HEIGHT (WHEELCHAIR ACCESSIBLE, AMBULATORY ACCESSIBLE SIM.)

ELEVATION

TOILET SEAT & GRAB BAR HEIGHT

PLAN

LAVATORY

SECTION


LAVATORY CLEARANCES

ELEVATION


LAVATORY & MIRROR HEIGHTS

ABOVE: T-SHAPED TURNING SPACE
BELOW: 67" DIA. TURNING SPACE

3 ADA REQUIREMENTS
1/4" = 1'-0"



2 ATRIUM / EDUCATION CENTER - MEZZANINE PLAN
3/16" = 1'-0"



1 ATRIUM / EDUCATION CENTER - FIRST FLOOR PLAN
3/16" = 1'-0"

GENERAL NOTES - FLOOR PLANS

- A. ALL DIMENSIONS FROM FACE OF STUD UNLESS CLEARLY NOTED OTHERWISE.
- B. WALL TYPES LISTED ON SHEET T1.3.
- C. FLOOR FINISH TRANSITIONS TO BE 1/4" MAX. BETWEEN FINISH HEIGHTS.
- D. PROVIDE WATER-RESISTANT GYP. BD. AT ALL BATHROOM WALL SURFACES UNLESS CLEARLY NOTED OTHERWISE. MAINTAIN FIRE-RESISTANCE RATING, WHERE REQ'D.
- E. CAULK PERIMETER OF ALL BACKSPASHES. CAULK JOINT TO BE CLEAR OR MATCH COLOR OF ADJ. WALL FINISH.
- F. SEE SHEET A7.1 FOR DOOR/WINDOW/FRAME ELEVATIONS, DOOR SCHEDULE AND WINDOW SCHEDULE.
- G. SEE ROOM FINISH SCHEDULE ON SHEET A7.1 FOR ALL INTERIOR FINISHES TO BE PROVIDED.
- H. MOVABLE FURNITURE SHOWN AS REFERENCE ONLY (NOT IN CONTRACT).
- I. PROVIDE CORNER GUARDS AT ALL INTERIOR OUTSIDE-CORNER APPLICATIONS EQUAL TO OR GREATER THAN 90 DEGREES.

KEYNOTES - FLOOR PLANS

- 1. ANIMAL PENS, PROVIDED AND INSTALLED BY OWNER.
- 2. CABLE CROSS BRACING, (SEE STRUCT.)
- 3. WATER FOUNTAIN, (SEE MECH.)
- 4. WASH BASIN, (SEE MECH.)
- 5. ELECTRICAL SUB PANEL, (SEE ELECT.)
- 6. HOSE BIB, (SEE MECH.)
- 7. 24" X 36" MIRROR, SEE ADA REQUIREMENTS FOR MOUNTING HEIGHTS.
- 8. ACCESSIBLE GRAB BARS, SEE ADA REQUIREMENTS FOR MOUNTING HEIGHTS.
- 9. PIPE BOLLARD, (SEE DETAIL 2/AC1.1)
- 10. BLEACHERS, PROVIDED AND INSTALLED BY OWNER.
- 11. STEEL COLUMN, (SEE STRUCT.)
- 12. ARENA AREA, GATES PROVIDED AND INSTALLED BY OWNER.
- 13. 42" H GUARD WALL WITH PAINTED WD. CAP. PAINT WHITE.
- 14. PRE-FINISHED METAL FASCIA.
- 15. WALL MOUNTED HEAT PUMP. MOUNT 8'-0" FROM F.F. (SEE MECH.)
- 16. MTL. PIPE HANDRAIL. PAINT BLACK.
- 17. SCRANTON OVERHEAD BRACED PLASTIC TOILET PARTITIONS IN SANDCASTLE ORANGE PEEL. SEE ELEVATIONS.
- 18. ELECTRIC HAND DRYER. (SEE ELECT.)
- 19. DONOR WALL. PROVIDED AND INSTALLED BY OWNER.
- 20. BID ALTERNATE #1 CONCRETE THROUGHOUT SHOW AREA. (SEE STRUCT.) FOR REQUIREMENTS. SEE SPECIFICATION FOR BID ALTERNATE EXPLANATION.
- 21. STAIR ENCLOSURE TO HAVE VAPOR BARRIER TOWARDS STAIR SIDE.
- 22. BABY CHANGING STATION.
- 23. INSULATED PIPE SLEEVE
- 24. V-SHAPED GYPSUM EXPANSION JOINT TRIM.
- 25. GYPSUM DEFLECTION BEAD WITH INTEGRAL GASKETING.


FLOOR PLAN LEGEND:

	INDICATES ACCESSIBLE ROOM
	INDICATES HEARING IMPAIRED ROOM. SEE ELECTRICAL.
	WALL TYPE, SEE SHEET T1.3.
	WINDOW / STOREFRONT TYPE, SEE SHEET A7.1.
	DOOR #. SEE SHEET A7.1.
	DOOR APPROACH FOR ADA CLEARANCES
	SHEAR WALL, SEE STRUCT.
	FLOOR DRAIN, SEE MECH.
	FLOOR SINK, SEE MECH.
	DOWNSPOUT

NOTE: NOT ALL DESIGNATIONS WILL APPEAR.



ARCHITECTURE & ENGINEERING
Located in Sioux Falls, Brookings & Mitchell South Dakota
designargroup.com 605.692.4008



DATE:	8/6/24
8/7/24	
REVISIONS:	
NO. DESCRIPTION:	1 Addendum #1
	2 Addendum #2

ENLARGED PLANS
SHEET NAME:
FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO.
OSE#: M2319-10X
SD STATE FAIR

LIVESTOCK PLAZA/SHEEP BARN


HURON, SD

PROJECT MANAGER:
NICK KUMMER


DATE:
07.17.2024

SHEET:


A3.2




1 BUILDING ELEVATION - NORTH
1/16" = 1'-0"



2 BUILDING ELEVATION - EAST
1/16" = 1'-0"



3 BUILDING ELEVATION - SOUTH
1/16" = 1'-0"



4 BUILDING ELEVATION - WEST
1/16" = 1'-0"

EXTERIOR MATERIALS SCHEDULE	
MARK	MATERIAL DESCRIPTION
CMU-1	SPLIT FACE CMU VENEER
MTL-1	METAL LINER PANEL
TR-1	WD. TRIM
TR-2	METAL TRIM

GENERAL NOTES - BUILDING ELEVATIONS


- A. EXTERIOR LIGHTING INDICATED FOR PLACEMENT ONLY. SEE ELEC. FOR LIGHTING SPECIFICATIONS.
- B. SEE SPECIFICATIONS FOR FULL REQUIREMENTS FOR EXTERIOR BUILDING MATERIALS. MATERIALS INDICATED GENERICALLY ON PLANS FOR CLARITY.

KEYNOTES - BUILDING ELEVATIONS

- 1. WOOD TRIM, PAINT TO MATCH METAL TRIM.
- 2. PIPE BOLLARD, PAINT HIGH VISIBILITY YELLOW.
- 3. SIGNAGE, (SEE ELEC.) FOR LIGHTING REQUIREMENTS. SIGNAGE PROVIDED AND INSTALLED BY OWNER.
- 4. SNOW GUARDS, (SEE SPEC'S)
- 5. METAL LOUVER, (SEE MECH.)
- 6. LIGHTING, (SEE ELEC.)



ARCHITECTURE & ENGINEERING
Located in Sioux Falls, Brookings & Mitchell South Dakota
designargroup.com 605.692.4008



DATE:	8/6/24
8/7/24	
REVISIONS:	
NO. DESCRIPTION:	1 Addendum #1
	2 Addendum #2

BUILDING ELEVATIONS
SHEET NAME:
FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO.
OSE#: M2319-10X
SD STATE FAIR

LIVESTOCK PLAZA/SHEEP BARN

HURON, SD

PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024

SHEET:


A4.1



ARCHITECTURE & ENGINEERING

Located in Sioux Falls, Brookings & Mitchell South Dakota

designargroup.com 605.692.4008



DATE: 8/7/24

REVISIONS: NO. DESCRIPTION: 2 Addendum #2

SHEET NAME: DETAILS

FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE


PROJECT NO. OSE#: M2319-10X
SD STATE FAIR

LIVESTOCK PLAZA/SHEEP BARN

HURON, SD
PROJECT MANAGER: NICK KUMMER


DATE: 07.17.2024

SHEET: A5.3




1 CLERESTORY - WINDOW/LOUVER DETAIL
1 1/2" = 1'-0"


AN ICE AND WATER MEMBRANE SHALL BE USED IN LIEU OF NORMAL UNDERLAYMENT AND EXTEND FROM THE EAVE'S EDGE A MINIMUM 36" BEYOND THE EXTERIOR WALL EDGE.




11 TYP. EAVE DETAIL
1 1/2" = 1'-0"




2 WALL @ ROOF DETAIL
1 1/2" = 1'-0"




3 TYP. CASED OPENING DETAIL @ HEAD
1 1/2" = 1'-0"




4 TYP. EAVE DETAIL @ ARENA
1 1/2" = 1'-0"




5 TYP. STONE CAP DETAIL
1 1/2" = 1'-0"




6 FOUNDATION DETAIL - TYP. ARENA
1 1/2" = 1'-0"




7 WALL OPENING & BOLLARD DETAIL
1 1/2" = 1'-0"




8 TYP. WALL CAP DETAIL
1 1/2" = 1'-0"




9 FOUNDATION DETAIL - TYP.
1 1/2" = 1'-0"




10 CLASS ROOM - BEAM DETAIL
1 1/2" = 1'-0"



12 FOUNDATION DETAIL @ STONE
1 1/2" = 1'-0"



13 TYP. THRESHOLD DETAIL @ EXTERIOR SLAB
1 1/2" = 1'-0"



14 CLASSROOM EAVE DETAIL
1 1/2" = 1'-0"

DATE PRINTED: 8/8/2024 9:21:11 AM



ARCHITECTURE & ENGINEERING

Located in Sioux Falls, Brookings & Mitchell South Dakota


designargroup.com 605.692.4008

GENERAL NOTES - FLOOR PLANS

- A. ALL DIMENSIONS FROM FACE OF STUD UNLESS CLEARLY NOTED OTHERWISE.
- B. WALL TYPES LISTED ON SHEET T1.3.
- C. FLOOR FINISH TRANSITIONS TO BE 1/4" MAX. BETWEEN FINISH HEIGHTS.
- D. PROVIDE WATER-RESISTANT GYP. BD. AT ALL BATHROOM WALL SURFACES UNLESS CLEARLY NOTED OTHERWISE. MAINTAIN FIRE-RESISTANCE RATING, WHERE REQ'D.
- E. CAULK PERIMETER OF ALL BACKSPASHES, CAULK JOINT TO BE CLEAR OR MATCH COLOR OF ADJ. WALL FINISH.
- F. SEE SHEET A7.1 FOR DOOR/WINDOW/FLOOR ELEVATIONS, DOOR SCHEDULE AND WINDOW SCHEDULE.
- G. SEE ROOM FINISH SCHEDULE ON SHEET A7.1 FOR ALL INTERIOR FINISHES TO BE PROVIDED.
- H. MOVABLE FURNITURE SHOWN AS REFERENCE ONLY (NOT IN CONTRACT).
- I. PROVIDE CORNER GUARDS AT ALL INTERIOR OUTSIDE-CORNER APPLICATIONS EQUAL TO OR GREATER THAN 90 DEGREES.

KEYNOTES - FLOOR PLANS

- 1. ANIMAL PENS, PROVIDED AND INSTALLED BY OWNER.
- 2. CABLE CROSS BRACING, (SEE STRUCT.)
- 3. WATER FOUNTAIN, (SEE MECH.)
- 4. WASH BASIN, (SEE MECH.)
- 5. ELECTRICAL SUB PANEL, (SEE ELECT.)
- 6. HOSE BIB, (SEE MECH.)
- 7. 24" X 36" MIRROR, SEE ADA REQUIREMENTS FOR MOUNTING HEIGHTS.
- 8. ACCESSIBLE GRAB BARS, SEE ADA REQUIREMENTS FOR MOUNTING HEIGHTS.
- 9. PIPE BOLLARD, (SEE DETAIL 2/AC1.1)
- 10. BLEACHERS, PROVIDED AND INSTALLED BY OWNER.
- 11. STEEL COLUMN, (SEE STRUCT.)
- 12. ARENA AREA, GATES PROVIDED AND INSTALLED BY OWNER.
- 13. 42" H GUARD WALL WITH PAINTED WD. CAP, PAINT WHITE.
- 14. PRE-FINISHED METAL FASCIA.
- 15. WALL MOUNTED HEAT PUMP, MOUNT 8'-0" FROM F.F. (SEE MECH.)
- 16. MTL PIPE HANDRAIL, PAINT BLACK
- 17. SCRANTON OVERHEAD BRACED PLASTIC TOILET PARTITIONS IN SANDCASTLE ORANGE PEEL. SEE ELEVATIONS.
- 18. ELECTRIC HAND DRYER, (SEE ELECT.)
- 19. DONOR WALL, PROVIDED AND INSTALLED BY OWNER.
- 20. BID ALTERNATE #1 CONCRETE THROUGHOUT SHOW AREA. (SEE STRUCT.) FOR REQUIREMENTS. SEE SPECIFICATION FOR BID ALTERNATE EXPLANATION.
- 21. STAIR ENCLOSURE TO HAVE VAPOR BARRIER TOWARDS STAIR SIDE.
- 22. BABY CHANGING STATION.
- 23. INSULATED PIPE SLEEVE
- 24. V-SHAPED GYPSUM EXPANSION JOINT TRIM.
- 25. GYPSUM DEFLECTION BEAD WITH INTEGRAL GASKETING.



REVISONS:	NO.	DESCRIPTION:	DATE:
	1	Addendum #1	8/6/24
	2	Addendum #2	8/7/24

SHEET NAME: INTERIOR ELEVATIONS

FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO. OSE#: M2319-10X
SD STATE FAIR


LIVESTOCK PLAZA/SHEEP BARN

HURON, SD


PROJECT MANAGER: NICK KUMMER

DATE: 07.17.2024


SHEET: A6.1




3 CLASS ROOM EXTERIOR ELEVATION - WEST
1/8" = 1'-0"




2 CLASS ROOM EXTERIOR ELEVATION - SOUTH
1/8" = 1'-0"




1 CLASS ROOM EXTERIOR ELEVATION - NORTH
1/8" = 1'-0"




8 WOMEN'S R.R.
1/4" = 1'-0"




7 MEN'S R.R.
1/4" = 1'-0"




6 MEN'S R.R.
1/4" = 1'-0"




5 MEN'S R.R.
1/4" = 1'-0"




4 MEN'S R.R.
1/4" = 1'-0"




13 CLASS ROOM - NORTH ELEVATION
3/16" = 1'-0"




12 DRINKING FOUNTAIN
1/4" = 1'-0"




11 WOMEN'S R.R.
1/4" = 1'-0"




10 WOMEN'S R.R.
1/4" = 1'-0"




9 WOMEN'S R.R.
1/4" = 1'-0"



16 CLASS ROOM - WEST ELEVATION
3/16" = 1'-0"



15 CLASS ROOM - SOUTH ELEVATION
3/16" = 1'-0"



14 CLASS ROOM - EAST ELEVATION
3/16" = 1'-0"

DOOR SCHEDULE										
MARK	ROOM	PANEL			Frame Type	Frame Material	Fire Rating	HARDWARE SET		COMMENTS
		TYPE	WIDTH	HEIGHT						
MAIN FLOOR PLAN										
101A	CLASSROOM	D2	6'-2"	7'-0"	S1	ALUM	NONE	1		
101B	CLASSROOM	D1	3'-0"	7'-0"	F1	HM	NONE	3		
101C	CLASSROOM	D1	3'-0"	7'-0"	F1	HM	NONE	3		
102A	HALL	D1	3'-0"	7'-0"	F1	HM	NONE	2		
102B	HALL	D1	3'-0"	7'-0"	F1	HM	NONE	2		INSULATED
102C	HALL	D1	3'-0"	7'-0"	F1	HM	NONE	3		
103	HALL	D1	3'-0"	7'-0"	F1	HM	NONE	5		
104	OFFICE	D1	3'-0"	7'-0"	F1	HM	NONE	4		
105	MEN'S	D1	3'-0"	7'-0"	F1	HM	NONE	6		
106	WOMEN'S	D1	3'-0"	7'-0"	F1	HM	NONE	6		
107	STAIR	D1	3'-0"	7'-0"	F1	HM	NONE	5		
O1	SHOW AREA	D3	12'-0"	12'-0"	---	WD	NONE			
O31	SHOW AREA	D3	12'-0"	12'-0"	---	WD	NONE			

GEN. NOTES - WINDOW & DOOR SCHEDULES

- A. ALL OPAQUE EXTERIOR MAN-DOORS ARE TO HAVE U-0.700 MAX. ASSEMBLY RATING.
- B. ALL OPAQUE EXTERIOR NON-SWINGING DOORS (OVHD, ETC.) ARE TO HAVE U-0.500 MAX. ASSEMBLY RATING.
- C. ALL ALUMINUM WINDOWS TO HAVE U-0.55 MAX. AND SHGC-0.40 MAX. ASSEMBLY RATINGS.
- D. ALL ALUMINUM ENTRANCE DOORS TO HAVE U-0.80 MAX. AND SHGC-0.40 MAX. ASSEMBLY RATINGS.
- E. ALL ALUMINUM CURTAINWALL/STOREFRONT GLAZING TO HAVE U-0.45 MAX. AND SHGC-0.40 MAX. ASSEMBLY RATINGS.
- F. SEE SPECIFICATIONS FOR DOOR HARDWARE SCHEDULE.


ROOM FINISH SCHEDULE										
ROOM NUMBER	ROOM NAME	FLOOR		WALL				CEILING		
		FIN	BASE	NORTH	EAST	SOUTH	WEST	FIN	HEIGHT	
Not Placed										
103	MECH.									
110	Room									
MAIN FLOOR PLAN										
101	CLASSROOM	CONC-2	VB-1	PNT-1	PNT-1	PNT-2	PNT-1	GYP	VARRIES	
102A	HALL	CONC-2	VB-1	PNT-1	PNT-1	PNT-1	PNT-1	ACT-1	9'-0"	
102B	HALL	CONC-2	VB-1	PNT-1	PNT-1	PNT-1	PNT-1	ACT-1	9'-0"	
103	MECH./ELEC.	CONC-2	VB-1	PNT-1	PNT-1	PNT-1	PNT-1	ACT-1	9'-0"	
103	MECH.	CONC-2	VB-1	PNT-1	PNT-1	PNT-1	PNT-1	ACT-1	9'-0"	
104	OFFICE	LVT-1	VB-1	PNT-1	PNT-1	PNT-1	PNT-1	ACT-1	9'-0"	
105	MEN'S	EPOXY	EPOXY	FRP-1/FRP-2	FRP-1/FRP-2	FRP-1/FRP-2	FRP-1/FRP-2	ACT-1	9'-0"	
106	WOMEN'S	EPOXY	EPOXY	FRP-1/FRP-2	FRP-1/FRP-2	FRP-1/FRP-2	FRP-1/FRP-2	ACT-1	9'-0"	
107	STAIR	LVT-1	---	MTL-1	---	MTL-1	MTL-1	GYP	9'-0"	
108	SHOW AREA	CONC-1	---	MTL-1/PLY-1	PLY-1	PLY-1	PLY-1	OPEN	VARRIES	
MEZZANINE										
201	VIEWING PLATFORM	LVT-1	---	MTL-1	MTL-1	MTL-1	MTL-1	OPEN	VARRIES	



ARCHITECTURE & ENGINEERING

Located in Sioux Falls, Brookings & Mitchell South Dakota


designargroup.com 605.692.4008




DATE: 8/6/24
8/7/24

REVISIONS:
NO. DESCRIPTION: 1 Addendum #1
2 Addendum #2


INTERIOR FINISH SCHEDULE			
CODE	DESCRIPTION	COLOR & MATERIAL SPECIFICATIONS	MANUFACTURER/SUPPLIER
ACT-1	2X2 ACOUSTICAL CEILING TILE	2X2, ASTRO CLIMAPLUS, EDGE DETAIL: SLT; DONN DX/DXL	USG
CONC-1	CONCRETE	BRUSHED FINISH	---
CONC-2	CONCRETE	POLISHED CONCRETE, LEVEL 3	---
EPOXY	EPOXY FLOOR COVERING W/ 6" COVE BASE	FOGGY MORNING - DECORATIVE RESINOUS FLOORING	SHERWIN WILLIAMS
FRP-1	FIBER-REINFORCED PLASTIC PANEL	FEATHER 0238	INPRO
FRP-2	FIBER-REINFORCED PLASTIC PANEL	PEBBLE GRAY 0387	INPRO
LVT-1	LUXURY VINYL TILE	CHAMPAGNE BEACH WOOD, 30 MIL, CLICK LOCK, WATERPROOF	LIFEPROOF
PL-1	HIGH-PRESSURE LAMINATE	FENIX J0754 BLU FES	FORMICA
PLY-1	SMOOTH FINISH PLYWOOD	3/4" THICK, 4'-0" FROM AFF	---
PNT-1	PAINT	SATIN FINISH, ORANGE PEAL TEXTURE, WILLOW SPRINGS PPG 1007-1	PPG PAINTS
PNT-2	PAINT	SATIN FINISH, ORANGE PEAL TEXTURE, BARK PPG1007-7	PPG PAINTS
PNT-3	PAINT, ALKYD FOR METAL SUBSTRATES	SATIN FINISH, SOLITARY STATE, PPG1009-4	PPG PAINTS
SS-1	SOLID SURFACE WINDOW SILLS	EVERFORM TAR COLLECTION, LUNA CONCRETE	FORMICA
VB-1	VINYL BASE	63 BURNT UMBER B	JOHNSONITE




2 FRAME ELEVATIONS
1/4" = 1'-0"



3 WINDOW ELEVATIONS
1/4" = 1'-0"



1 DOOR ELEVATIONS
1/4" = 1'-0"



4 STOREFRONT ELEVATIONS
1/4" = 1'-0"

SHEET NAME:
SCHEDULES & DOOR ELEVATIONS

PROJECT NO.
OSE#: M2319-10X
SD STATE FAIR

LIVESTOCK PLAZA/SHEEP BARN

HURON, SD





PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024




SHEET:

A7.1


FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE





1 STOREFRONT @ INSUL. WALLS - DETAIL
3" = 1'-0"



2 STOREFRONT @ NON INSUL. WALLS
3" = 1'-0"



3 HM DOOR @ NON INSUL. WALLS
3" = 1'-0"



4 ALUM. WINDOW/DOOR @ MASONRY WALLS
3" = 1'-0"


DATE PRINTED: 8/8/2024 9:21:17 AM



ARCHITECTURE & ENGINEERING

Located in Sioux Falls, Brookings & Mitchell South Dakota

designarcgroup.com 605.692.4008



DATE: 8/7/24

REVISIONS: NO. 2 DESCRIPTION: Addendum #2

SHEET NAME: **DOOR & WINDOW DETAILS**

FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO. OSE#: M2319-10X SD STATE FAIR


LIVESTOCK PLAZA/SHEEP BARN

HURON, SD PROJECT MANAGER: NICK KUMMER


DATE: 07.17.2024

SHEET: **A7.2**


DATE PRINTED: 8/8/2024 9:21:17 AM




1 EXISTING SHED - DEMO PLAN
3/32" = 1'-0"




7 WALL TYPES - SHED RELOCATION
1 1/2" = 1'-0"




2 RELOCATED SHED - NORTH HALF PLAN
3/32" = 1'-0"




3 RELOCATED SHED - SOUTH HALF PLAN
3/32" = 1'-0"



4 SHED HALF - EAST ELEV.
1/8" = 1'-0"



5 SHED HALF - END ELEV.
1/8" = 1'-0"



6 SHEDHALF - WEST ELEV.
1/8" = 1'-0"

GENERAL NOTES - BUILDING RELOCATION


- 1 A. GENERAL CONTRACTOR TO CONTRACT WITH A MOVING COMPANY. (SEE SPECIFICATIONS) CONTRACTOR TO COORDINATE EXISTING FOUNDATION DEMOLITION AND PROJECT SCHEDULE WITH MOVING COMPANY.
- 2 B. APPLY NEW SIDING, ROOFING, AND FLASHING PER MANUFACTURERS STANDARDS.
- 3 C. MTL-2 TO CLOSELY MATCH EXISTING METAL SIDING AND ROOFING. COORDINATE EXACT COLOR AND MATERIAL WITH OWNER.



ARCHITECTURE & ENGINEERING

Located in Sioux Falls, Brookings & Mitchell South Dakota

designargroup.com 605.692.4008



REVISIONS:	NO.	DESCRIPTION:	DATE:
	1	Addendum #1	8/6/24
	2	Addendum #2	8/7/24

SHEET NAME:
EXISTING SHED RELOCATION PLAN

FULL-SCALE: 22x34
HALF-SCALE: 11x17
DRAWING MAY NOT BE PRINTED TO SCALE

PROJECT NO.
OSE#: M2319-10X
SD STATE FAIR


LIVESTOCK PLAZA/SHEEP BARN



HURON, SD
PROJECT MANAGER:
NICK KUMMER

DATE:
07.17.2024


SHEET:

R-A1.1






UNDERFLOOR WASTE PLUMBING PLAN
SCALE: 1/16" = 1'-0"



Architecture | Planning | Interiors
830 2nd Street South
Brookings, SD 57006 | P: 605.692.4008
2301 W Russell St, Suite 1
Sioux Falls, SD 57104 | P: 605.692.4008

PRO ENGINEERING INC.
CONSULTING ENGINEER
LOREN SCHOENEMAN
406 SOUTH 2ND AVE, SUITE 102
SIOUX FALLS, SOUTH DAKOTA 57104
PHONE: 605-336-6248, FAX: 605-335-1191



REVISIONS: NO. DESCRIPTION:	DATE:


SHEET NAME:
UNDERFLOOR WASTE PLUMBING PLAN

PRO ENG. PROJECT NO.
Pe-2407
LIVESTOCK PLAZA SHEEP BARN


PROJECT MANAGER:
LRS

DATE:
7.17.24

SHEET:
M1.1




WATER PIPING PLAN
SCALE: 1/16" = 1'-0"



Architecture | Planning | Interiors
830 2nd Street South
Brookings, SD 57006 | P: 605.692.4008
2301 W Russell St, Suite 1
Sioux Falls, SD 57104 | P: 605.692.4008

PRO ENGINEERING INC.
CONSULTING ENGINEER
LOREN SCHOENEMAN
406 SOUTH 2ND AVE, SUITE 102
SIOUX FALLS, SOUTH DAKOTA 57104
PHONE: 605-336-6248, FAX: 605-335-1191



REVISIONS: NO. DESCRIPTION:	DATE:

SHEET NAME:
WATER PIPING PLAN

PRO ENG. PROJECT NO.
Pe-2407
LIVESTOCK PLAZA SHEEP BARN

PROJECT MANAGER:
LRS


DATE:
7.17.24

SHEET:
M1.2



Architecture | Planning | Interiors
 830 2nd Street South
 Brookings, SD 57006 | P: 605.692.4008
 2301 W Russell St, Suite 1
 Sioux Falls, SD 57104 | P: 605.692.4008

PRO ENGINEERING INC.
 CONSULTING ENGINEER
 LOREN SCHOENEMAN
 406 SOUTH 2ND AVE, SUITE 102
 SIOUX FALLS, SOUTH DAKOTA 57104
 PHONE: 605-336-6248, FAX: 605-335-1191



REVISIONS:	DATE:
NO. DESCRIPTION:	


SHEET NAME:
HVAC PLANS

PRO ENG. PROJECT NO.
 Pe-2407
 LIVESTOCK PLAZA
 SHEEP BARN


PROJECT MANAGER:
 LRS

DATE:
 7.17.24

SHEET:
M2.1



HVAC ROOF PLAN
 SCALE: 1/16" = 1'-0"



HVAC PLAN -OFFICE CLASSROOMS
 SCALE: 1/16" = 1'-0"

CONDENSATE DRAIN
 FC-2 PIPE CONDENSATE DOWN AND SPILL ON GRADE.
 FC-1 PIPE CONDENSATE THROUGH WALL AND SPILL ON EXTERIOR GRADE.
 FC-3 AND FC-4 PIPE CONDENSATE THROUGH WALL AND SPILL TO MOP SINK.
 FC-5 PIPE CONDENSATE DOWN TO FLOOR DRAIN BELOW FAN COIL.